



ELECTRONICS, INC.
 44 FARRAND STREET
 BLOOMFIELD, NJ 07003
 (973) 748-5089
<http://www.nteinc.com>

NTE133

N-Channel JFET Silicon Transistor General Purpose AF Amplifier TO106 Type Package

Absolute Maximum Ratings: ($T_A = +25^\circ\text{C}$ unless otherwise specified)

Drain-Source Voltage, V_{DS}	25V
Drain-Gate Voltage, V_{DG}	25V
Gate-Source Voltage, V_{GS}	-25V
Gate Current, I_G	10mA
Total Device Dissipation ($T_A = +25^\circ\text{C}$), P_D	300mW
Derate Above 25°C	2mW/ $^\circ\text{C}$
Operating Junction Temperature Range, T_J	-55° to $+150^\circ\text{C}$
Storage Temperature Range, T_{stg}	-55° to $+150^\circ\text{C}$
Lead Temperature (During Soldering, 1/16" from case for 10sec), T_L	$+260^\circ\text{C}$

Electrical Characteristics: ($T_A = +25^\circ\text{C}$ unless otherwise specified)

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
Gate-Source Breakdown Voltage	$V_{(BR)GSS}$	$I_G = 1^\circ\text{A}$, $V_{DS} = 0$	-25	-	-	V
Gate Reverse Current	I_{GSS}	$V_{GS} = 20\text{V}$, $V_{DS} = 0$	-	-	-1	nA
		$V_{GS} = 20\text{V}$, $V_{DS} = 0$, $T_A = +150^\circ\text{C}$	-	-	-1	$^\circ\text{A}$
Gate-Source Cutoff Voltage	$V_{GS(off)}$	$I_D = 1^\circ\text{A}$, $V_{DS} = 15\text{V}$	-	-	-6.5	V
Gate-Source Voltage	V_{GS}	$I_D = 50^\circ\text{A}$, $V_{DS} = 15\text{V}$	-0.4	-	-6.0	V
Zero-Gate-Voltage Drain Current	I_{DSS}	$V_{DS} = 15\text{V}$, $V_{GS} = 0$	0.5	-	15	mA
Forward Transfer Admittance	$ y_{fs} $	$V_{DS} = 15\text{V}$, $V_{GS} = 0$, $f = 1\text{kHz}$	1000	-	7500	$^\circ\text{mho}$

