XZCC8FDM30V

Female, M8, 3 pin, straight connector, cable gland M9.5 x 1



Main	
Range of Product	Telemecanique Cabling components
Accessory / separate part category	Cabling accessories
Accessory / Separate Part Type	Connector
Electrical connection	Straight female connector M8, 3 pins
Collar material	Metal
Status LED	Without
Cable connection	Vampire clip 0.00 in² (0.25 mm²) 0.20 in (5 mm)

Complementary

o o mpromornary		
Cable gland type	M9.5	
Cable connector fixing	Screw-on	
[Ue] rated operational voltage	60 V AC 75 V DC	
Line Rated Current	4 A	
Enclosure Material	Plastic	
Minimum insulating resistance	1 GΩ	
Contact resistance	10000 μOhm	
Net Weight	0.02 lb(US) (0.01 kg)	

Environment

IP Degree of Protection	IP67
Ambient Air Temperature for Operation	-13158 °F (-2570 °C)

Ordering and shipping details

Category	22483-MACHINE CABLES	
Discount Schedule	DS3	
GTIN	3389110834710	
Nbr. of units in pkg.	1	
Package weight(Lbs)	0.49 oz (14.0 g)	
Returnability	No	
Country of origin	DE	

Packing Units

Unit Type of Package 1	PCE	
Package 1 Height	0.94 in (2.4 cm)	
Package 1 width	4.96 in (12.6 cm)	
Package 1 Length	1.30 in (3.3 cm)	
Unit Type of Package 2	S01	
Number of Units in Package 2	50	
Package 2 Weight	32.63 oz (925.0 g)	
Package 2 Height	5.91 in (15 cm)	
Package 2 width	5.91 in (15 cm)	
Package 2 Length	15.75 in (40 cm)	-

Offer Sustainability


to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov	
[™] REACh Declaration	
Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration	
Yes	
₽¥Yes	

Warranty	18 months	

Product data sheet Dimensions Drawings

XZCC8FDM30V

Dimensions



(1) Cable gland: M9.5 x 1

Product data sheet Connections and Schema

XZCC8FDM30V

Connections and Schemes

