

QUICK START GUIDE FOR DEMONSTRATION CIRCUIT 997

10/12 BIT 250, 210 AND 170 MSPS ADC

LTC2242-12/10, LTC2241-12/10 OR LTC2240-12/10

DESCRIPTION

Demonstration circuit 997 supports a family of 10/12 BIT 250, 210 and 170 MSPS ADCs. Each assembly features one of the following devices: LTC2242-12, LTC2241-12, LTC2240-12, LTC2242-10, LTC2241-10 or LTC2240-10 high speed, high dynamic range ADCs.

The versions of the 997B demo board that support the LTC2242 family of 10 and 12 BIT A/D converters are listed in Table 1. Depending on the required resolution and sample rate the DC997 is supplied with the appropriate A/D. The circuitry on the analog inputs is optimized for analog input frequencies from 10 MHz to 250 MHz.

Design files for this circuit board are available. Call the LTC factory.

LTC is a trademark of Linear Technology Corporation

Table 1. DC997B Variants

DC997 VARIANTS	ADC PART NUMBER	RESOLUTION	MAXIMUM SAMPLE RATE	INPUT FREQUENCY
997B-A	LTC2242-12	12-Bit	250Msps	10MHz < A _{IN} < 250MHz
997B-B	LTC2241-12	12-Bit	210Msps	10MHz < A _{IN} < 250MHz
997B-C	LTC2240-12	12-Bit	170Msps	10MHz < A _{IN} < 250MHz
997B-D	LTC2242-10	10-Bit	250Msps	10MHz < A _{IN} < 250MHz
997B-E	LTC2241-10	10-Bit	210Msps	10MHz < A _{IN} < 250MHz
997B-F	LTC2240-10	10-Bit	170Msps	10MHz < A _{IN} < 250MHz

QUICK START GUIDE FOR DEMONSTRATION CIRCUIT 997

10/12 BIT 250, 210 AND 170 MSPS ADC

Table 2. Performance Summary (T_A = 25°C)

PARAMETER	CONDITION	VALUE
Supply Voltage	Depending on sampling rate and the A/D converter provided, this supply must provide up to 500mA.	3.3V ±0.3V (10%); The 2.5V supply required by the ADC is regulated locally by U8 from the 3.3V
Analog input range	Depending on Sense Pin Voltage (at converter inputs)	1V _{PP} to 2V _{PP}
Logic Input Voltages: OE, $\overline{\text{SHDN}}$	Minimum Logic High	1.7V
	Maximum Logic Low	0.7V
Logic Output Voltage (FIN1108T LVDS Buffer)	Minimum Logic High @ -3.4mA w/100Ω Termination	1.2V +170mV
	Maximum Logic Low @ +3.4mA w/100Ω Termination	1.2V – 170mV
Sampling Frequency (Convert Clock Frequency)	See Table 1	
Encode Clock Level	50 Ω Source Impedance. (Convert Clock input is capacitor coupled on board and terminated with 50Ω.)	0.2V _{p-p} ⇔ 2.5V _{p-p} Sine Wave or Square wave
Resolution	See Table 1	
Input frequency range	See Table 1	
SFDR	See Applicable Data Sheet	
SNR	See Applicable Data Sheet	

QUICK START PROCEDURE

Demonstration circuit 997 is easy to set up to evaluate the performance of any of the LTC2242 family of High Speed LVDS output A/D converters - LTC2242-12,

LTC2241-12, LTC2240-12, LTC2242-10, LTC2241-10 or LTC2240-10. Refer to Figure 1 for proper measurement equipment setup and follow the procedure below:




Figure 1. DC997 Setup

JUMPERS

The DC997 demonstration circuit board should have the following jumper settings:

□ JP2 - MODE:

- VDD: 2's complement & disable Clock Duty Cycle Stabilizer (Default for LTC2240, 2241)
- 2/3: 2's complement & Clock Duty Cycle Stabilizer on (Default for LTC2242)
- 1/3: Offset Binary & Clock Duty Cycle Stabilizer on
- GND: Offset Binary & Clock Duty Cycle Stabilizer off

□ JP3:

- SHDN & OE GND: Normal operation (Default)
- SHDN GND & OE Vdd: Normal operation with high output impedance
- SHDN Vdd & OE GND: Nap Mode with high output impedance
- SHDN Vdd & OE Vdd: Sleep Mode with high output impedance

□ JP4 - SENSE:

- Select 2.5V for the 2Vpp input range (Default)
- Select VCM for the 1Vpp input range

POWER

If a DC890B is used to acquire data from the DC997, the DC890B should be connected to a USB port and provided an external 6V, 1Amp power supply. The DC890B will not enable LVDS mode without externally applied power present. Apply +3.3V across the pins marked "+3.3V" and "GND" on the DC997. The DC997 demonstration circuit requires up to 500 mA depending on the sampling rate and the A/D converter supplied.

While the DC890B data collection board is initially powered by the USB cable, it requires an external power supply of 6V on the 2.1mm power jack or the adjacent turrets (+) and (-) before the DC890B will enable LVDS mode.

ENCODE CLOCK

NOTE: THIS IS NOT A LOGIC LEVEL INPUT. Apply an encode clock to the SMA connector on the DC997 demonstration circuit board marked "ENCODE CLK". Refer to Table 2 for recommended level, impedance and coupling. For the best noise performance (SNR AND SFDR), the ENCODE CLK must be driven with a very low jitter source. When using a sinusoidal generator, the amplitude should be large, up to 2.5V_{P-P}. Using bandpass filters on the ENCODE CLK and the Analog input [AIN] will improve the noise performance by reducing the wideband noise power of the signals. Data sheet FFT plots are taken with 10 pole LC filters made by TTE (Los Angeles, CA) to suppress signal generator harmonics, non-harmonically related spurs and broad band noise. The very high sampling bandwidth of the LTC2242 family of parts will fold multiple Nyquist bands of noise (if present) down to base band raising the noise floor.

[The LTC2242 family of ADCs provides a flexible Encode Clock interface capable of accommodating both single ended and differential sources from LVDS or sinusoidal inputs. See the LTC2242 data sheet for other Encode Clock drive options.]

ANALOG INPUT NETWORK

The input transformer and the RC network on the analog inputs are optimized for 10 to 250MHz. These

components must be optimized for higher or lower input frequencies. Consult the LTC2242 data sheet for other frequency ranges.

Apply the analog input signal of interest to the SMA connector on the DC997 demonstration circuit board marked "AIN". This input is capacitive coupled to the input of a MaCom ETC1-1-13 balun or a flux coupled ETC1-1T transformer. (See Schematic)

DIGITAL OUTPUTS

The LVDS conversion clock output is available on pins [50, 52] of J2. The LVDS data samples are available on Pins [8-46, 56-82] for 12 BITS or [8-46, 56-70] for 10 BITS as LVDS pairs isolated by a ground pin between each set. The data samples can be collected via a logic analyzer, cabled to a development system through a SHORT 100 pin ribbon cable (available from Samtec - HSC8 series of high speed connectors) or directly via a DC890B FastDAACS data collection system.

SOFTWARE

The DC890B is controlled by the *PScope System Software* provided or downloaded from the Linear Technology website at <http://www.linear.com/software/>. If a DC890B was provided, follow the DC890 Quick Start Guide and the instructions below.

To start the data collection software if "*PScope.exe*", is installed (by default) in \Program Files\LTC\PScope\, double click the PScope Icon or bring up the run window under the start menu and browse to the PScope directory and select PScope.

If the DC997 demonstration circuit is properly connected to the DC890, PSCOPE should automatically detect the DC997, and configure itself accordingly. If necessary the procedure below explains how to manually configure PSCOPE.

Under the "Configure" menu, go to "ADC Configuration...." Check the "Config Manually" box and use the following configuration options, see Figure 2:

Bits: 12 (or 10 for 10 bits parts)

Alignment: 15
FPGA Ld: LVDS
Channs: 1
Bipolar: Checked
Positive-Edge Clk: Unchecked

When evaluating 10 BIT performance using a 12 BIT part, select the 10 Bit part and PScope will automati-

cally blank the last two LSBs when using a DC997 supplied with a 12 BIT ADC.

If everything is hooked up properly, powered and a suitable convert clock is present, clicking the “Collect” button should result in time and frequency plots displayed in the PScope window. Additional information and help for *PScope* is available in the DC890B Quick Start Guide and in the online help available within the *PScope* program itself.





Figure 2. ADC Configuration

QUICK START GUIDE FOR DEMONSTRATION CIRCUIT 997

10/12 BIT 250, 210 AND 170 MSPS ADC



REVISION HISTORY	
ECO REVISION	DESCRIPTION
1	INITIAL RELEASE
2	DATE APPROVED: 8/29/2006
3	DATE APPROVED: 8/29/2006
4	DATE APPROVED: 8/29/2006
5	DATE APPROVED: 8/29/2006
6	DATE APPROVED: 8/29/2006
7	DATE APPROVED: 8/29/2006
8	DATE APPROVED: 8/29/2006
9	DATE APPROVED: 8/29/2006
10	DATE APPROVED: 8/29/2006
11	DATE APPROVED: 8/29/2006
12	DATE APPROVED: 8/29/2006
13	DATE APPROVED: 8/29/2006
14	DATE APPROVED: 8/29/2006
15	DATE APPROVED: 8/29/2006
16	DATE APPROVED: 8/29/2006
17	DATE APPROVED: 8/29/2006
18	DATE APPROVED: 8/29/2006
19	DATE APPROVED: 8/29/2006
20	DATE APPROVED: 8/29/2006
21	DATE APPROVED: 8/29/2006
22	DATE APPROVED: 8/29/2006
23	DATE APPROVED: 8/29/2006
24	DATE APPROVED: 8/29/2006
25	DATE APPROVED: 8/29/2006
26	DATE APPROVED: 8/29/2006
27	DATE APPROVED: 8/29/2006
28	DATE APPROVED: 8/29/2006
29	DATE APPROVED: 8/29/2006
30	DATE APPROVED: 8/29/2006
31	DATE APPROVED: 8/29/2006
32	DATE APPROVED: 8/29/2006
33	DATE APPROVED: 8/29/2006
34	DATE APPROVED: 8/29/2006
35	DATE APPROVED: 8/29/2006
36	DATE APPROVED: 8/29/2006
37	DATE APPROVED: 8/29/2006
38	DATE APPROVED: 8/29/2006
39	DATE APPROVED: 8/29/2006
40	DATE APPROVED: 8/29/2006
41	DATE APPROVED: 8/29/2006
42	DATE APPROVED: 8/29/2006
43	DATE APPROVED: 8/29/2006
44	DATE APPROVED: 8/29/2006
45	DATE APPROVED: 8/29/2006
46	DATE APPROVED: 8/29/2006
47	DATE APPROVED: 8/29/2006
48	DATE APPROVED: 8/29/2006
49	DATE APPROVED: 8/29/2006
50	DATE APPROVED: 8/29/2006
51	DATE APPROVED: 8/29/2006
52	DATE APPROVED: 8/29/2006
53	DATE APPROVED: 8/29/2006
54	DATE APPROVED: 8/29/2006
55	DATE APPROVED: 8/29/2006
56	DATE APPROVED: 8/29/2006
57	DATE APPROVED: 8/29/2006
58	DATE APPROVED: 8/29/2006
59	DATE APPROVED: 8/29/2006
60	DATE APPROVED: 8/29/2006
61	DATE APPROVED: 8/29/2006
62	DATE APPROVED: 8/29/2006
63	DATE APPROVED: 8/29/2006
64	DATE APPROVED: 8/29/2006
65	DATE APPROVED: 8/29/2006
66	DATE APPROVED: 8/29/2006
67	DATE APPROVED: 8/29/2006
68	DATE APPROVED: 8/29/2006
69	DATE APPROVED: 8/29/2006
70	DATE APPROVED: 8/29/2006
71	DATE APPROVED: 8/29/2006
72	DATE APPROVED: 8/29/2006
73	DATE APPROVED: 8/29/2006
74	DATE APPROVED: 8/29/2006
75	DATE APPROVED: 8/29/2006
76	DATE APPROVED: 8/29/2006
77	DATE APPROVED: 8/29/2006
78	DATE APPROVED: 8/29/2006
79	DATE APPROVED: 8/29/2006
80	DATE APPROVED: 8/29/2006
81	DATE APPROVED: 8/29/2006
82	DATE APPROVED: 8/29/2006
83	DATE APPROVED: 8/29/2006
84	DATE APPROVED: 8/29/2006
85	DATE APPROVED: 8/29/2006
86	DATE APPROVED: 8/29/2006
87	DATE APPROVED: 8/29/2006
88	DATE APPROVED: 8/29/2006
89	DATE APPROVED: 8/29/2006
90	DATE APPROVED: 8/29/2006
91	DATE APPROVED: 8/29/2006
92	DATE APPROVED: 8/29/2006
93	DATE APPROVED: 8/29/2006
94	DATE APPROVED: 8/29/2006
95	DATE APPROVED: 8/29/2006
96	DATE APPROVED: 8/29/2006
97	DATE APPROVED: 8/29/2006
98	DATE APPROVED: 8/29/2006
99	DATE APPROVED: 8/29/2006
100	DATE APPROVED: 8/29/2006

CUSTOMER NOTICE	
LINEAR TECHNOLOGY HAS MADE A BEST EFFORT TO DESIGN A CIRCUIT THAT MEETS THE SPECIFICATIONS AND CONDITIONS LISTED IN THIS QUICK START GUIDE. HOWEVER, THE USER MUST VERIFY THE CIRCUIT OPERATION IN THE ACTUAL APPLICATION, COMPONENT SUBSTITUTION AND PRINTED CIRCUIT BOARD LAYOUT MAY SIGNIFICANTLY AFFECT CIRCUIT PERFORMANCE OR RELIABILITY. CONTACT LINEAR TECHNOLOGY APPLICATIONS ENGINEERING FOR ASSISTANCE SUPPLIED FOR USE WITH LINEAR TECHNOLOGY PARTS	<p>CONTRACT NO. APPROVALS</p> <p>DESIGNER: []</p> <p>CHECKED: []</p> <p>APPROVED: []</p> <p>DATE: 8/29/2006</p>
<p>TITLE: SCHEMATIC</p> <p>LT2242 FAMILY LUDS BUS</p> <p>SIZE: []</p> <p>DWG NO. []</p> <p>DATE: 8/29/2006</p>	<p>REVISION: []</p> <p>DATE: []</p> <p>BY: []</p> <p>DESCRIPTION: []</p>



