



- 1 PINS: 0.00076[.000030] MINIMUM GOLD IN CONTACT AREA, 0.00381[.000150] MIN TIN ON SOLDER TAILS, ALL OVER 0.00127[.000050] MINIMUM NICKEL. STACKING CLIPS; NICKEL PLATED ONLY.
- 2. CUSTOMER TO PROVIDE CARD GUIDANCE SYSTEM
- 3 DATUMS AND BASIC DIMENSIONS ESTABLISHED BY CUSTOMER
- 4. CONNECTOR REQUIRES USE OF 2 - SIZE 2M SCREWS FOR FASTENING TO PRINTED CIRCUIT BOARD
- 5 ASSEMBLY KEYED FOR 5 VOLT CARDS
- 6 RECESSED AMP AND CSA LOGOS LOCATED ON BOTH SIDES OF THE HOUSING
- 7 MATERIAL: HOUSING & ORGANIZER; LCP; COLOR, BLACK
PIN; BRASS & PHOSPHOR BRONZE
STACKING CLIP; PHOSPHOR BRONZE

**COPYRIGHT 2005
 TYCO ELECTRONICS CORP
 ALL RIGHTS RESERVED**

VOLTAGE KEYING	1,17,34 35,51,68	ALL OTHER PINS	36,67	5146046-1
	5.0 [.197]	4.25 [.167]	3.5 [.138]	PART NUMBER
"L" (PIN LENGTH) AND LOCATION				
THIS DRAWING IS A CONTROLLED DOCUMENT.				
DIMENSIONS:		TOLERANCES UNLESS OTHERWISE SPECIFIED:		TYCO Electronics Corporation Harrisburg, PA 17105-3608
0 PLC	± .013 [0.005]	1 PLC	± .013 [0.005]	NAME: M. WALSMLEY PRODUCT SPEC: STACKED PIN HEADER ASSEMBLY, 136 POSN, TOP BD MTG, THRU-HOLE, WITH 2 STACKING CLIPS, RAISED & STANDARD HEIGHT, AMP MEMORY CARD APPLICATION SPEC: SIZE: A1 CAGE CODE: 00779 DRAWING NO: 5146046 RESTRICTED TO: CUSTOMER DRAWING
2 PLC	± .013 [0.005]	3 PLC	± .013 [0.005]	
4 PLC	± .013 [0.005]	5 PLC	± .013 [0.005]	
6 PLC	± .013 [0.005]	7 PLC	± .013 [0.005]	
MATERIAL:	FINISH:	WEIGHT:	SCALE:	REV: 0
		18.5 GRAMS	4:1	