


1. Wiring Diagram.



2. Cable test condition :

Open / Short : 100%
 Insulation resistance : 5M ohms
 Contact resistance : 2 ohm
 Hipot : DC 300V / 1 sec

3. Each pcs with PE polybag.

5	CONN	USB3.0 MICRO B MALE G/F BLACK	1	P2
4	PVC	45P PVC BLACK OVERMOLD	25g	
3	PE	LLDPE 500026 6201	16g	
2	CONN	USB3.0 A/M G/F BLUE	1	P1
1	CABLE	《28AWG (7/0.12TC) *P+D(7/0.10TC)+AL+M》*2+28AWG (7/0.12TC) *IP+24AWG(7/0.2TC)*2C+A+D+B (96/0.12AM) OD5.5 BLACK	1	500mm
NO.	PART NO.	DESCRIPTION		
		BILL OF MATERIAL		

A	INITIAL RELEASE	2014/08/28
REVISION#	DESCRIPTION	DATE
	103-1092-BL-00050	REV A
CNC Tech, LLC		
DRAWN	WENC	DATE
CHECKED	EDWIN	08/24/14
APPROVAL		
CUSTOMER P/N:		
CUSTOMER:		
TITLE	CABLE USB3.0 A/M TO MICRO B MALE	
SHEET	1 OF 1	
		REV A