

BT series
TIMER BTM-S

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 16
 D-32758 Detmold
 Germany
 Fon: +49 5231 14-0
 Fax: +49 5231 14-292083
 www.weidmueller.com



The BTM timing relay has 8 different timing functions which can be set via a rotary switch on the front. Delay/clock times can be selected between 0.1 second and 120 hours.

The component has an additional control input on the input side which must be activated for the respective timing function.

The timing relay is built into an Insta enclosure just 17.5 mm wide.

On the output side there is a relay contact with a switching capacity of 250 V/ 5 A.

General ordering data

Order No.	8647700000
Type	TIMER BTM-S
Version	BT series, Timing relay, No. of contacts: 1, CO contact, AgNi 90/10, Rated control voltage: 24...230 V AC, 24...48 V DC, Continuous current: 5 A, Screw connection
GTIN (EAN)	4032248308903
Qty.	10 pc(s).

**BT series
TIMER BTM-S**

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 16
 D-32758 Detmold
 Germany
 Fon: +49 5231 14-0
 Fax: +49 5231 14-292083
 www.weidmueller.com

Technical data**Ratings**

Conductor connection system	Screw connection	Humidity	35...85 % rel. humidity, no condensation
UL 94 flammability rating	V-2		

Dimensions and weights

Width	17.5 mm	Height	80 mm
Depth	73 mm	Net weight	78.9 g

Temperatures

Operating temperature	-10 °C...+55 °C	Storage temperature	-25 °C...+65 °C
-----------------------	-----------------	---------------------	-----------------

Input

Rated control voltage	24...230 V AC, 24...48 V DC	Power rating	≤ 0.4 VA, 1.6 W
Time ranges	0.10 s - 120 h	Repeat accuracy	± 1 %

Output

Max. switching voltage, AC	250 V	Continuous current	5 A
----------------------------	-------	--------------------	-----

Contact specifications

No. of contacts	1	Contact design	CO contact
Contact material	AgNi 90/10	Mechanical service life	10 ⁷ switching cycles (no load, 1800/h)
Electrical service life, DC coil	10 ⁵ switching cycles (5A at 250 Vac, ohm load at 1800/h)	Contact resistance	100 MΩ min., at 500 V DC

Insulation coordination

Protection degree	IP 30 // terminals IP 20
-------------------	--------------------------

Other technical data

Version	Timing relay
---------	--------------

Further details of approvals / standards

Certificate No. (UR)	E223474OMR	Standards	UL508
----------------------	------------	-----------	-------

Rated data UL

Certificate No. (UR)	E223474OMR
----------------------	------------

Classifications

ETIM 2.0	EC001439	ETIM 3.0	EC001439
UNSPSC	30-21-19-17	eClass 4.1	27-14-23-10
eClass 5.1	27-14-23-10	eClass 6.0	27-14-23-10
eClass 7.0	27-14-23-10		

Data sheet...

**BT series
TIMER BTM-S**

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 16
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com

Technical data

Approvals

Approvals



Downloads

Declaration of Conformity [K258_08_03.pdf](#)