

K MOPL K51 STAHL

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 16
 D-32758 Detmold
 Germany
 Fon: +49 5231 14-0
 Fax: +49 5231 14-292083
 www.weidmueller.com



For many years, the name Klippon® has stood for competence and quality in enclosures. The enclosures are ideal for turnkey customised solutions for standard industrial applications and for explosive-risk applications.

Improved products that meet all application requirements: this was Weidmüller's aim during the update of the Klippon® K housing series. Weidmüller delivers many types of aluminium enclosures; they are designed to fit precisely with a wide range of customer requirements and applications.

Our comprehensive product line provides the following advantages:

- Available in two different surfaces: natural and powder-coated (RAL 7001)
- Available normally with silicone or chloroprene gasket seal
- A uniform Torx-slotted screw head is used for over 19 different housing sizes.
- Mounting holes not within the sealed area
- High degree of protection: IP66, IP67 and IP68
- Impact resistance of up to 10 Joules
- The housings are certified by ATEX, GOST, GOST Ex, cULus, Russian Maritime Register, German Lloyd, as well as the empty housing standard.
- Alloy is resistant to salt water

- Standardised distributor housings with threaded holes and a variety of terminal configurations

General ordering data

| | |
|------------|---|
| Type | MOPL K51 STAHL |
| Order No. | 3073090000 |
| Version | Mounting plate, Mounting Plate, Sheet steel, galvanised, 207 mm |
| GTIN (EAN) | 4008190858025 |
| Qty. | 1 pc(s). |

Data sheet

K MOPL K51 STAHL

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 16
 D-32758 Detmold
 Germany
 Fon: +49 5231 14-0
 Fax: +49 5231 14-292083
 www.weidmueller.com

Technical data

Dimensions and weights

| | | | |
|------------|--------|----------------------------|--------|
| Width | 207 mm | Mounting dimension - width | 193 mm |
| Net weight | 327 g | | |

General information

| | | | |
|--------------------|---------|----------|-------------------------|
| Material thickness | 2 mm | Material | Sheet steel, galvanised |
| Impact resistance | 10.00 J | | |

General information on accessories

| | | | |
|----------------------------|-------------------------|--------------------|---------|
| Material | Sheet steel, galvanised | Material thickness | 2 mm |
| Mounting dimension - width | 193 mm | Type of fixing | Screwed |

Classifications

| | | | |
|------------|-------------|------------|-------------|
| ETIM 3.0 | EC000318 | UNSPSC | 31-16-23-03 |
| eClass 5.1 | 27-18-92-07 | eClass 6.2 | 27-18-92-61 |
| eClass 7.1 | 27-18-92-61 | | |

Approvals

| | |
|-----------|---------|
| Approvals | |
| ROHS | Conform |