


T491V477K006ZT

Obsolete

B45194E, Tantalum, MnO2 Tantalum, 470 uF, 10%, 6.3 VDC, SMD, Molded, Low Profile, 7343, Height Max = 2mm



General Information		
Series	B45194E	
Dielectric	MnO2 Tantalum	
Style	SMD Chip	
Description	SMD, Molded, Low Profile	
Features	Low Profile	
RoHS	Yes	
Termination	Tin	
AEC-Q200	No	
Notes	Obsolete. Old Part Number [Obsolete] Was B45194E1477K409.	

Dimensions		
Footprint	7343	
L	7.3mm +/-0.3mm	
W	4.3mm +/-0.3mm	
Н	2mm MAX	
S	1.3mm +/-0.3mm	
F	2.4mm +/-0.1mm	
K	1.7mm TYP	

Specifications				
Capacitance	470 uF			
Capacitance Tolerance	10%			
Voltage DC	6.3 VDC (85C), 4.22 VDC (125C)			
Temperature Range	-55/+125°C			
Rated Temperature	85°C			
Dissipation Factor	15%			
Failure Rate	N/A			
Leakage Current	29.6 uA			

Packaging Specifications			
Packaging	T&R, 178mm		
Packaging Quantity	1000		

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.