TERMINATIONS & BUNDLING



Military Spec Silicone Tape

FireFlex[®] self-fusing silicone tape is a unique adhesive free product that quickly fuses to itself to create

a moisture and corrosion resistant continuous seal for electrical insulation, pipe and hose repair, or anywhere a quick and residue free wrap is needed.

FireFlex® Silicone Tape creates an airtight/watertight seal around even irregularly shaped applications, and the high insulation values make it useful in repairing cracked or damaged insulation in Class A and B applications.

Resistant to engine fluids, solvents, high-heat, and molten metal splashes, FireFlex[®] tape can withstand the harshest of environments. A wide operating temperature of -85°F to 500°F makes it excellent for automotive, industrial, and marine applications, as well as a perfect end termination for our FireFlex® Silicone Sleeving.

Ideal to keep in a toolbox for emergency repairs on wires or hoses, as a residue free solution to coil extension cords, ropes, and cables, and for a waterproof, heat, and chemical resistant wrap for wiring harnesses and splices.



GARDEN



Part

STA1.00BK36

STA1.00RD36

STB1.00BK36

SRA1.00BK36

SRA1.00RD36

SRB1.00BK36

Width

1"

1″

1″

1″

1"

1″



Wall

Thickness

0.020"

0.020"

0.040"

0.020"

0.020"

0.040"

COMPUTERS





PLUMBING

Class

Α

Α

В

Α

Α

В

Type

Triangular

Triangular

Triangular

Rectangle

Rectangle

Rectangle



Available

Colors

BK

RD

BK

ВК

RD

BK





Roll

36'

36'

36'

36'

36'

36'



HOME



Lbs/

Roll

0.29

0.33

0.57

0.45

0.50

0.75

Class B applications. CLASS* 20,000 HR LIFE TEMP. А 221°F (105°C) 266°F (130°C) В

*The temperature classification indicates the maximum (hot-spot) temp. at which the insulation system can be operated for normal expected service life.



Rectangle

1 (833) SLEEVING www.techflex.com

- A-A-59163
- Mil-I-46852
- Self-Fusing
- Air & Moisture Tight Seal
- Prevents Corrosion
- No Adhesive, Bonds **Only to Itself**
- Resists Weathering
- Conforms to Irregular Shapes
- Elastic Memory Seal
- Cures in 24 Hours at **Room Temperature**



Colored guide line only on triangular type tapes

INSULATION CLASS

May be used in many Class A &