

Data sheet | Item number: 280-352

End and intermediate plate; 2.5 mm thick; light gray

www.wago.com/280-352



Data

Physical data

Width	2.5 mm / 0.098 inches
Height	75 mm / 2.953 inches

Subject to changes. Please also observe the further product documentation!

WAGO GmbH & Co. KG
Hansastr. 27
32423 Minden
Phone: +49571 887-0 | Fax: +49571 887-169
Email: info.de@wago.com | Web: www.wago.com

Do you have any questions about our products?
We are always happy to take your call at +49 (571) 887-44222.



Depth	28 mm / 1.102 inches
-------	----------------------

Material Data

Note (material data)

Information on material specifications can be found here

Color	light gray
Material group	I
Insulation material	Polyamide (PA66)
Flammability class per UL94	V0
Fire load	0.122 MJ
Weight	3.3 g

Environmental requirements

Processing temperature	-35 ... +85 °C
Continuous operating temperature	-60 ... +105 °C

Commercial data

Product Group	1 (Rail Mounted Terminal Blocks)
eCl@ss 10.0	27-14-11-33
eCl@ss 9.0	27-14-11-33
ETIM 8.0	EC000886
ETIM 7.0	EC000886
PU (SPU)	100 (25) pcs
Packaging type	box
Country of origin	CN
GTIN	4017332199209
Customs tariff number	8538909990

Environmental Product Compliance

RoHS Compliance Status	Compliant, No Exemption
------------------------	-------------------------

Required accessories

End plate

Through terminal block	<p>Item no.: 280-999</p> <p>4-conductor through terminal block; 2.5 mm²; suitable for Ex e II applications; center marking; for DIN-</p>
------------------------	--

www.wago.com/280-999

Subject to changes. Please also observe the further product documentation!

WAGO GmbH & Co. KG
Hansastr. 27
32423 Minden
Phone: +49571 887-0 | Fax: +49571 887-169
Email: info.de@wago.com | Web: www.wago.com

Do you have any questions about our products?
We are always happy to take your call at +49 (571) 887-44222.



rail 35 x 15 and 35 x 7.5; CAGE CLAMP®; 2,50 mm²; light gray

Item no.: 280-994

4-conductor through terminal block; 2.5 mm²; suitable for Ex e II applications; center marking; for DIN-rail 35 x 15 and 35 x 7.5; CAGE CLAMP®; 2,50 mm²; light gray www.wago.com/280-994

Double potential terminal block

Item no.: 280-995

Double potential terminal block; 2.5 mm²; suitable for Ex e II applications; with double, center marker slot; for DIN-rail 35 x 15 and 35 x 7.5; CAGE CLAMP®; 2,50 mm²; light gray www.wago.com/280-995

Ground terminal block

Item no.: 280-677/999-950

4-conductor ground terminal block; 2.5 mm²; suitable for Ex e II applications; center marking; for DIN-rail 35 x 15 and 35 x 7.5; CAGE CLAMP®; 2,50 mm²; green-yellow www.wago.com/280-677/999-950

Item no.: 280-837/999-950

4-conductor ground terminal block; 2.5 mm²; suitable for Ex e II applications; center marking; for DIN-rail 35 x 15 and 35 x 7.5; CAGE CLAMP®; 2,50 mm²; green-yellow www.wago.com/280-837/999-950

Downloads

Documentation

Bid Text

280-352 X81 - Datei	2019 年2月19 日	xml 2.6 kB	Download
------------------------	--------------	---------------	----------

280-352 doc - Datei	2017 年4月28 日	doc 22.5 kB	Download
------------------------	--------------	----------------	----------

Additional Information

	pdf 2.3 MB	Download
--	---------------	----------

CAD/CAE-Data

CAE data

EPLAN Data Portal 280-352	URL	Download
---------------------------	-----	----------

WSCAD Universe 280-352	URL	Download
------------------------	-----	----------

ZUKEN Portal 280-352	URL	Download
----------------------	-----	----------

CAD data

2D/3D Models 280-352	URL	Download
----------------------	-----	----------

Subject to changes. Please also observe the further product documentation!

WAGO GmbH & Co. KG
 Hansastr. 27
 32423 Minden
 Phone: +49571 887-0 | Fax: +49571 887-169
 Email: info.de@wago.com | Web: www.wago.com

Do you have any questions about our products?
 We are always happy to take your call at +49 (571) 887-44222.



Environmental Product Compliance

Compliance Search

Environmental Product Compliance 280-352	URL	Download
End and intermediate plate; 2.5 mm thick; light gray		

Installation Notes

Subject to changes. Please also observe the further product documentation!