



DASH

VOLTAGE: 300 V TEMPERATURE: 80°C

CABLE TYPE / SIZE: SILICONE INSULATION SILICONE JACKET CABLE, 50/0.18 STRANDING,

16 AWG(1.25 mm²) x 2C

CABLE JACKET COLOR: BLACK

CONDUCTORS COLOR: BLUE, BROWN OVERALL LENGTH (L): 1830 + 100,-0 mm

END 'A' TERMINATION: STRAIGHT FEMALE BARREL 5.5 x 2.1 x 11 mm

(SPRING LOADED WITH LOCKING NOTCH)

END 'B' TERMINATION: STRIP & TIN

STRAIN RELIEF: SR FOR GTM21097 TYPE

APPROVALS CABLE: DESIGN TO MEET UL, CSA or cUL

APPROVALS CONNECTOR: N/A

PACKING:

(YELLOW)

BULK PACKED, BUNDLES OF 25. MAXIMUM SHIPPING CARTON WEIGHT IS 30 KG.

NOTE:

CORD, PLUG AND CONNECTOR MUST BE MARKED WITH APPROVAL SYMBOLS OR FILE NUMBER(S) IF APPLICABLE.



Contents of this document

prior notice

are subject to change without





Foot Note:	Limitation of U
Globtek Inc. will not be liable for the	Globtek produc
safety and performance of these power	mission critical
product if unauthorized access and repair	hazardous envir
occurs. End user should consult the applica-	aircraft applica
ble UL,CSA or EN Standards for proper	approval from t
inctellation instruction	I

ct are not authorized for use as components in life support, ronment, nuclear or ations without prior written the CEO of Globtek Inc.

DASH NO.	I	PART NO	REV.	DESCRIPTION					NOTES	
TABULATION BLOCK										
			.xx +/- 0.01 + .xxx +/005		ANGULAR +/- 1°		lobTek [®] , Inc	186 Veterans Dr. No Tel. 201-784-1000		
INIT.BY:	CII	DATE 01/20/10	.x +/	METERS /- 1.0 -/- 0.5	ANGULAR +/- 1°	DWG TITLE: SILICONE JACKET OUTPUT CABLE ASSEMBLY WITH STRAIN RELIEF				
DRAWN:	INF	DATE: 01/20/10	FSCN G, CC		SIZE A				REV. B	
APRVD:	LIM	DATE: 01/20/10	SCAl	SCALE: NONE		PART NO:	CCP6166FSILI	-SR(R)	SHEET 1/1	