## ATGBICS FTL410QE4N Finisar Compatible Transceiver QSFP+ 40GBase-SR4 (850nm, MMF, 150m, MTP/MPO, DOM, Ind Temp)

Brand : ATGBICS

Product code: FTL410QE4N-C

Product name : FTL410QE4N Finisar Compatible Transceiver QSFP+ 40GBase-SR4 (850nm, MMF, 150m, MTP/MPO, DOM, Ind Temp)

FTL410QE4N Finisar Compatible Transceiver QSFP+ 40GBase-SR4 (850nm, MMF, 150m, MTP/MPO, DOM, Ind Temp)


ATGBICS FTL410QE4N Finisar Compatible Transceiver QSFP+ 40GBase-SR4 (850nm, MMF, 150m, MTP/MPO, DOM, Ind Temp):

ATGBICS FTL410QE4N 40GBase-SR4 supports a distance of up to 150m over multi-mode fibre (MMF) using a wavelength of 850nm via an MPO connector. Digital optical monitoring (DOM) support is also present enabling real-time monitoring of the parameters of the fibre optic transceiver. Our product meets the specification of FTL410QE4N= and we proudly offer a compatibility guarantee and lifetime warranty. Our rigorously tested products record a unique traceable serial number and are fully compliant with all MSA Standards.





Performance		Power	
SFP transceiver type *Fiber opticMaximum data transfer rate *40000 Mbit/sInterface type *QSFP+	40000 Mbit/s	Input voltage Maximum voltage Power consumption (typical)	3.3 V 3.5 V 3.5 W
Single-mode fiber (SMF) supported Multi-mode fiber (MMF) supported Fiber optic connector SFP transceiver standard Maximum transfer distance Wavelength Ethernet LAN	Iti-mode fiber (MMF) supported   Iti-mode fiber (MMF) supported     er optic connector   MPO     P transceiver standard   SR4     ximum transfer distance   150 m     welength   850 nm     hernet LAN   Image: Application of the standard sta	Operational conditions Minimum operating temperature Maximum operating temperature Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H)	-5 °C 85 °C -5 - 85 °C -40 - 85 °C 0 - 95% 0 - 95%
Digital Diagnostics Monitoring (DDM) Wavelength-division multiplexing (WDM)		<b>Weight &amp; dimensions</b> Width Depth Height	13.5 mm 72.4 mm 18.4 mm
Features		Weight	42 g
Product colour Silver   Housing material Metal   Plug and Play ✓   Hot-Plug support ✓		Packaging data Number of products included Package type	1 pc(s) Box
Hot-swap	China Finisar CE, FCC, RoHS	Technical details	
Easy to install Country of origin Brand compatibility Certification		Sustainability compliance Sustainability certificates Doesn't contain	✔ RoHS Lead



5056468761996

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.