## 0.25 METER LENGTH



Connector A 132117RP SMA Jack Straight Brass Gold + Heatshrink 50 Ohm RG-316 Continuity/Hi-Pot Connector B 000-69475 BNC Plug Straight Brass Nickel

## Assembly & Label Notes

Assembly label to be placed ~ 2" from end of connector A and/ or heat shrink Assembly shall be built with SN96.5 LEAD FREE solder. See Routing Notes for additional assembly & testing instructions.

|  | Connector A   |   |   | Cable  |  |  | Connector B   |           |  |
|--|---|---|---|--|--|--|---|-----------|--|
|  | Part #:<br>Description:<br>Type:<br>Gender:<br>Body Type:<br>Contact Type:<br>Polarity:<br>Impedance:<br>Mounting:<br>Body Material:<br>Body Finish:<br>IP Rating:<br>Contact Material:<br>Contact Finish:<br>Max. Freq.:<br>Booting: | 132117RP<br>SMA JACK RP R<br>SMA<br>Jack<br>Straight<br>Crimp<br>Reverse<br>50 Ohm<br>Cable<br>Brass<br>Gold<br>None<br>Brass<br>Gold<br>12.4 GHz<br>SMA Jack Straigh | G316 50O  | Part #:<br>Description:<br>Dielectric:<br>Shielding:<br>Diameter:<br>Impedance:<br>Sheathing:<br>Testing:<br>Length: | RG-316<br>RG-316 - ST 0.102<br>ST<br>Braid<br>0.102<br>50 Ohm<br>None<br>Continuity Hi-Pot<br>0.25 Meter | Part #:<br>Description:<br>Type:<br>Gender:<br>Body Type:<br>Contact Type:<br>Polarity:<br>Impedance:<br>Mounting:<br>Body Material:<br>Body Material:<br>Body Finish:<br>IP Rating:<br>Contact Material:<br>Contact Finish:<br>Max. Freq.:<br>Booting:<br>Clocking: | 000-69475<br>BNC Clamp PLUG f<br>BNC<br>Plug<br>Straight<br>Solder<br>Standard<br>50 Ohm<br>Cable<br>Brass<br>Nickel<br>None<br>Brass<br>Silver<br>4 GHz<br>BNC Plug Straight<br>0° | RG188 50O |  |
| Amphenol THIS DRAWING MAY CONTAPROPRIETARY INFORMATIO   FOR ANY PURPOSE DETRIMINOL FOR ANY PURPOSE DETRIMINOL   CONTROLLED DOCUMENT - DO NOT COPY IN ANY FORM WITHOUT THI   CUSTOM CABLE CONTROLLED DOCUMENT - DO NOT COPY |   |   | AND MUST NOT BE US<br>TAL TO CUSTOM CAB<br>CED OR TRANSCRIBEJ<br>/RITTEN CONSENT OF<br>NCE OF THIS DRAWIN | LE<br>D<br>JG Part No:   | NC-ST-PL G316 0.25M  |  | UNLESS SPECIFIED<br>TOLERANCE:<br>0-18 inches +/- 1/2"<br>over 18" +/- 2%<br>ASSEMBLY:<br>CENTER LABEL IF LENGTH<br>IS LESS THAN 12 INCHES  |           |  |



## **RoHS 2015/863 Compliance Statement**

According to the manufacture of all the component parts contained in this assembly, this product has been determined to be RoHS Compliant with RoHS Directive 2011/65/EU and as amended by Directive 2015/863, and without material exceptions (RoHS3 Complaint).

For the individual component RoHS certificates used in this assembly, please contact Amphenol Custom Cable.

The RoHS Compliance of any product so designated is based upon evidence from the producer (manufacturers') that the component parts comply with the RoHS Directive. Amphenol Custom Cable has taken all reasonable steps to confirm that the OEM (Manufacturer) of the components used in this assembly have provided evidence regarding the absence of the restricted substances to support the manufacturer's claim of compliance.

To the best of our knowledge and with due diligence, we certify that the product listed herein complies with the RoHS requirements.

Date: 10/1/2023

Part Number: Q-7100J0005.25M

Manufacturer: Amphenol Custom Cable

Description: SMA-ST-JK-RP/BNC-ST-PL G316 0.25M

This information is valid as of the date indicated for the item (part number) listed.

**Director of Quality Assurance** 

Janice Frank