



FEATURES

- (2) Slide Out Trays with Spring Loaded Stop Latch
- Holds (4) LGX Adapter Plates, Cassettes, or Modules
- Built In Raised Splice Tray Mounting Bracket
- Multiple Tie Downs and Cable Retention Brackets
- Hinged Front and Rear Removable Doors, Lexan Doors Available
- Order Preloaded with Terminated Cables, Adapters, Pigtails or Cassettes
- Rugged 14 Gauge Aluminum, Available in Black or Off-White (BW)

The 4RU FIS Patch and Splice Panel accommodates (4) LGX adapter panels, modules or cassettes. The 2 sliding trays on the top and bottom of the enclosure allow for easy access to both the patch bay and splice bay. Multiple cable retention brackets, splice tray mounts and tie down spots allow for convenient cable management. Rack mount installs into a standard 19" rack with included mounting hardware. Adapter panels, splice trays and 23" mounting brackets are sold separately.

SPECIFICATIONS

Dimensions	17"W x 14"D x 7.125"H
Capacity	Up to 24 (6 Pack) or 32 (8 Pack) Simplex Connections Up to 48 (6 Pack) Duplex Connections (LC or SC)
Material	.060" Aluminum
Coatings	Electro-statically Applied Powder Coat, Available in Black or Off White

ORDERING INFORMATION

F1RMSP4RU4X	4RU Patch and Splice Enclosure, 4 Plate, Solid Front/Rear Doors, Black
F1RMSP4RU4XL	4RU Patch and Splice Enclosure, 4 Plate, Smoked Lexan Front/Sold Rear Doors, Black
F1RMSP4RU4X-BW	4RU Patch and Splice Enclosure, 4 Plate, Solid Front/Rear Doors, Off White
F1RMSP4RU4XL-BW	4RU Patch and Splice Enclosure, 4 Plate, Smoked Lexan Front/Sold Rear Doors, Off White

ACCESSORIES (PURCHASED SEPARATELY)

4RURACK-ADP23	4RU and 8RU 23" Rack Mounting Brackets, Pair, Black
4RURACK-ADP23BW	4RU and 8RU 23" Rack Mounting Brackets, Pair, Off White
F1-SPL12	Metal Splice Tray, 12 Position Fusion Splice Chip, 6.5"L x 4.7"W x .42"H
F1-SPL24	Metal Splice Tray, 24 Position Fusion Splice Chip, 11.72"L x 3.99"W x .42"H
F1-6808	Plastic Splice Tray, 12 Position Fusion Splice Chip, 7.1"L x 4.25"W x .48"H
F1-6707BLKF	Metal Splice Tray, 12 Position Fusion Splice Chip, 7.5"L x 4"W x .63"H
F1-13189	Cable Retention Rings For 4RU & 8RU Interconnect - 10 pack

TECH DRAWINGS

