


## Protect It! 6-Outlet Surge Protector, 6 ft. (1.83 m) Cord, 790 Joules, Diagnostic LED, TAA

MODEL NUMBER: TLP606TAA



### Highlights

- Compliant with the Federal Trade Agreements Act (TAA) for GSA Schedule purchases
- 6 outlet / 6-ft. cord
- 790 joule rating

### Package Includes

- TLP606TAA surge suppressor
- Instruction manual with warranty information

### Description

Tripp Lite's TLP606TAA is compliant with the Federal Trade Agreements Act (TAA) for GSA Schedule purchases. It offers economical AC surge suppression for protection of workstations, desktop PCs, telecom systems and other sensitive electronics. Built-in AC surge suppression shields connected equipment from damage and performance problems due to transient surges. Automatic shutoff permanently cuts power to outlets if protection circuit is incapacitated, preventing equipment damage and indicating replacement is required. TLP606TAA offers 6 total outlets, 6-ft. (1.83 m) cord and diagnostic LED to warn of suppressor damage. AC suppression rated at 790 joules shields equipment from surges and line noise. Attractive white suppressor housing with keyhole mounting tabs offer convenient protection of desktop computer equipment and accessories. \$20,000 Ultimate Lifetime Insurance (U.S., Canada, and Puerto Rico only).

PLUG/OUTLETS: Input: NEMA5-15P/Output: 6 NEMA5-15R/6-ft. (1.83 m) AC line cord

ELECTRICAL: 120V AC, 60Hz, 15A (Requires NEMA5-15R wall receptacle)

FORMAT: Corded multi-outlet strip with 1 transformer spaced outlet

SUPPRESSION: AC: 150V RMS Clamping/790 joules/330V UL1449 3RD EDITION

### Features

- Compliant with the Federal Trade Agreements Act (TAA) for GSA Schedule purchases
- 6 outlets
- 6-ft. (1.83 m) cord
- Surge suppression rating: 790 joules
- EMI/RFI noise filtering
- 15 amp resettable circuit breaker
- Automatic shutoff permanently cuts power to outlets if protection circuit is incapacitated, preventing equipment damage and indicating replacement is required
- Green protection LED
- Includes full normal mode (H-N) and common mode (N-G/H-G) line surge suppression
- Can accommodate 1 large transformer plug without covering remaining outlets, 3 total transformers
- Keyhole support for wall mounting
- Lighted power switch
- \$20,000 Ultimate Lifetime Insurance (U.S., Canada, and Puerto Rico only)

## Specifications

| <b>OVERVIEW</b>                              |   |
|--|---|
| UPC Code                                     | 037332159250  |
| <b>INPUT</b>                                 |   |
| Nominal Input Voltage(s) Supported           | 120V AC   |
| Recommended Electrical Service               | 120V (110-125V)   |
| Input Cord Gauge Type                        | 14 gauge; SJT   |
| Input Cord Gauge (AWG)                       | 14  |
| Voltage Compatibility (VAC)                  | 120   |
| Input Plug Type                              | NEMA 5-15P  |
| Input Cord Details                           | SJT   |
| Input Cord Length (ft.)                      | 6   |
| Right-Angle Plug                             | No  |
| Input Cord Length (m)                        | 1.83  |
| Integrated Cord Clip                         | No  |
| <b>OUTPUT</b>                                |   |
| Frequency Compatibility                      | 60 Hz   |
| Output Receptacles                           | (6) 5-15R   |
| Circuit Breaker (amps)                       | 15  |
| Overload Protection                          | 15A resettable illuminated combo switch / circuit breaker                         |
| Transformer Accommodation                    | (2) Yes   |
| Outlet Orientation                           | Single row of 6 outlets   |
| Right-Angle Outlets                          | No  |
| <b>USER INTERFACE, ALERTS &amp; CONTROLS</b> |   |
| Diagnostic LED(s)                            | Yes   |
| Switches                                     | Combination AC circuit breaker and 2 position red illuminated on/off power switch |
| Diagnostic LED Details                       | Built-in LED confirms suppressor "protection present" (green) status              |
| <b>SURGE / NOISE SUPPRESSION</b>             |   |
| AC Suppression Joule Rating                  | 790   |
| AC Suppression Response Time                 | < 1 ns  |

|  |   |
|--|---|
| Protection Modes   | Includes full normal mode (H-N) and common mode (N-G / H-G) line suppression  |
| UL1449 Let Through Rating                                  | 400V - UL Verified  |
| EMI / RFI Filtering  | Yes   |
| Automatic Shut-Off   | No  |
| <b>DATALINE SURGE SUPPRESSION</b>                          |   |
| Cable (Coax) Protection                                    | No  |
| Network (Ethernet) Protection                              | No  |
| Telephone/DSL Protection                                   | No  |
| <b>PHYSICAL</b>  |   |
| Material of Construction                                   | Plastic   |
| Power Cord Color   | Light Gray  |
| Housing Color  | Gray  |
| Mounting Holes or Slots                                    | Yes   |
| Receptacle Color   | Light gray  |
| Shipping Dimensions (hwd / in.)                            | 14.90 x 1.61 x 8.48   |
| Shipping Dimensions (hwd / cm)                             | 37.85 x 4.09 x 21.54  |
| Shipping Weight (lbs.)                                     | 1.33  |
| Shipping Weight (kg)                                       | 0.60  |
| Unit Dimensions (hwd / in.)                                | 10.800 x 1.850 x 1.230  |
| Unit Dimensions (hwd / cm)                                 | 3.20 x 4.19 x 26.67   |
| Unit Weight (lbs.)   | 1.08  |
| Unit Weight (kg)   | 0.49  |
| <b>FEATURES &amp; SPECIFICATIONS</b>                       |   |
| Antimicrobial  | No  |
| Rotatable Outlets  | No  |
| <b>STANDARDS &amp; COMPLIANCE</b>                          |   |
| Product Certifications                                     | CAN/CSA-C22.2 No. 269.3 (Canada); CAN/CSA-C22.2 No. 308 (Canada); cUL Listed; NOM (Mexico); UL 1449; UL 1363; UL Listed     |
| Product Compliance   | RoHS; Trade Agreements Act (TAA)  |
| <b>WARRANTY &amp; SUPPORT</b>                              |   |
| Product Warranty Period (Worldwide)                        | Lifetime limited warranty   |
| Connected Equipment Insurance (U.S., Canada & Puerto Rico) | \$20,000 <a class="insuranceLink" href="//www.tripplite.com/support/insurance-policy">Ultimate Lifetime Insurance</a>&nbsp; |



1000 Eaton Boulevard  
Cleveland, OH 44122  
United States



© 2022 Eaton. All Rights Reserved.  
Eaton is a registered trademark. All other trademarks  
are the property of their respective owners.