


# INDUSTRIAL 3.5" QUAD CORE SBC


## conga-JC370




- Highest Performance 3.5" Single Board Computer
- 8<sup>th</sup> Generation Intel® Core™ SOC processors with up to 4 cores
- Intel® UHD-Graphics 610/620, up to 24 Execution Units
- Up to 64 GByte dual channel DDR4 2400 MT/s
- Multiple Expansion card sockets
- Flexible internal and external Video interfaces
- Wide Range Power Input 12 – 24V
- congatec embedded Board Controller Features

<b>Formfactor</b>	Industrial 3.5" Juke Board   146 x 102 mm (~ 5.75" x 4.02")					
<b>CPU</b>	Intel® Core™ i7-8665UE	4 Cores   8 Threads	1.7 GHz   4.4 GHz (turbo)	8 MB Cache	15 W TDP (12.5-25W cTDP)	
	Intel® Core™ i5-8365UE	4 Cores   8 Threads	1.6 GHz   4.1 GHz (turbo)	6 MB Cache	15 W TDP (12.5-25W cTDP)	
	Intel® Core™ i3-8145UE	2 Cores   4 Threads	2.2 GHz   3.9 GHz (turbo)	4 MB Cache	15 W TDP (12.5-25W cTDP)	
	Intel® Celeron® 4305UE	2 Cores   2 Threads	2.0 GHz	2 MB Cache	15 W TDP	
<b>DRAM</b>	Dual channel DDR4 up to 2400 MT/s   2x SO-DIMM   up to 2x 32 GByte					
<b>Chipset</b>	Integrated in SoC					
<b>Ethernet</b>	Intel® 2.5GbE with TSN support under Linux / Intel® 1GbE with AMT support (AMT with i7 or i5 only)					
<b>Audio</b>	High Definition Audio   Realtek ALC888S-VD Audio Codec					
<b>Graphics</b>	Intel® UHD-Graphics 610/620 Graphics, up to 24 Execution Units					
<b>Expansion Sockets</b>	M.2 key M size 2280 (PCIe x4/SATA)   M.2 key B size 2242/3042 (PCIe/USB/SIM)   M.2 key E size 2230 (PCIe/CNVio/USB)   miniPCIe card slot full/half-size (PCIe/SATA/USB/opt. SIM)   microSIM card slot					
<b>Internal Connectors</b>	LVDS 24bit Dual channel (or opt. eDP)   opt. 2nd LVDS via external adapter   Backlight (power/control)   SATA/eSATA/SATADOM   Disk Power 5V   Dual USB 2.0   Audio Front Panel (HPout/MIC)   LINEout and DMIC   COM port (RS232/422/485)   Two 4 pin COM ports (RS232)   8 bit general purpose I/O   Management I/O (opt. 8 GPIOs)   I <sup>2</sup> C/SM Bus   Front panel (power switch, LEDs, reset,...)   Power DC In (12-24 V)   RTC battery   Intrusion (case open)   FAN (4pin)					
<b>External Connector (Front Panel)</b>	DisplayPort++   USB 3.1 Gen.2 Type C (PD and DP Alt. Mode)   Dual USB 3.1 Gen.2 Type A   Dual LAN RJ45   COM DE9 RS232/422/485					
<b>congatec embedded Board Controller</b>	Multi Stage Watchdog   non-volatile User Data Storage   Manufacturing and Board Information   Board Statistics   I <sup>2</sup> C bus (fast mode, 400 kHz, multi-master)   Power Loss Control   Hardware Health Monitoring   POST Code redirect					
<b>Embedded BIOS</b>	AMI Aptio® 2.X (UEFI) BIOS   SM-BIOS   BIOS Update   Logo Boot   Quiet Boot   HDD Password					
<b>Security</b>	Trusted Platform Module (TPM 2.0)   Secure Root of Trust   Secure Memory Encryption   Secure Encrypted Virtualization					
<b>Power Specification</b>	Power Supply 12-24V   Power Management   ACPI S3/S4/DeepS5   Wake on time from S5   FAN monitored & controlled   see user's guide for full details					
<b>Operating Systems</b>	Microsoft® Windows 10 (64bit only)   Microsoft® Windows 10 IoT Enterprise (64bit only)   Linux					
<b>Temperature</b>	Operating Temperature: 0 to +60°C		Storage Temperature: -20 to +70°C			
<b>Extended Temperature</b>	Screening service on request:		-25 to +80°C (burn-in & cold-soak) -40 to +85°C (burn-in & cold-soak)			
<b>Humidity</b>	Operating: 10 - 90% r. H. non cond.		Storage: 5 - 95% r. H. non cond.			
<b>Size</b>	146 x 102 mm (~ 5.75" x 4.02")					

# conga-JC370 | Connectors



# conga-JC370 | Block diagram



# conga-JC370 | Order Information

Article	PN	Description
conga-JC370/i7-8665UE	054001	3.5" SBC based on Intel® Core™ i7-8665UE quad core processor with 1.7GHz, 8MB Intel® Smart Cache, Intel® UHD Graphics 620 and 2400MT/s dual channel DDR4 memory interface (Whiskey Lake-UE)
conga-JC370/i5-8365UE	054002	3.5" SBC based on Intel® Core™ i5-8365UE quad core processor with 1.6GHz, 6MB Intel® Smart Cache, Intel® UHD Graphics 620 and 2400MT/s dual channel DDR4 memory interface (Whiskey Lake-UE)
conga-JC370/i3-8145UE	054003	3.5" SBC based on Intel® Core™ i3-8145UE dual core processor with 2.2GHz, 4MB Intel® Smart Cache, Intel® UHD Graphics 620 and 2400MT/s dual channel DDR4 memory interface (Whiskey Lake-UE)
conga-JC370/4305UE	054005	3.5" SBC based on Intel® Celeron® 4305UE dual core processor with 2.0GHz, 2MB Intel® Smart Cache, Intel® UHD Graphics 610 and 2133MT/s dual channel DDR4 memory interface (Whiskey Lake-UE)
conga-JC370/CSA-B	054050	Standard active cooling solution and integrated 12V fan for conga-JC370 (borehole)
conga-JC370/CSA-T	054051	Standard active cooling solution and integrated 12V fan for conga-JC370 (threaded)
conga-JC370/CSP-B	054052	Standard passive cooling solution for conga-JC370 (borehole)
conga-JC370/CSP-T	054053	Standard passive cooling solution for conga-JC370 (threaded)
conga-JC370/HSP-B	054054	Standard heatspreader solution for conga-JC370 (borehole)
conga-JC370/HSP-T	054055	Standard heatspreader solution for conga-JC370 (threaded)
DDR4-SODIMM-2400 (4GB)	068790	DDR4 SODIMM memory module with 2400 MT/s and 4GB RAM
DDR4-SODIMM-2400 (8GB)	068791	DDR4 SODIMM memory module with 2400 MT/s and 8GB RAM
DDR4-SODIMM-2400 (16GB)	068792	DDR4 SODIMM memory module with 2400 MT/s and 16GB RAM
DDR4-SODIMM-2666 (32GB)	068806	DDR4 SODIMM memory module with 2666 MT/s and 32GB RAM
cab-Backlight ZHR-8, Open End	14000253	Cable for Backlight connector and Open End, 50cm, for conga-JC370
cab-LVDS SHDR-40V, Open End	14000254	Cable for LVDS Panel with JST SHDR-40V connector and Open End, 50cm, for conga-JC370
cab-Backlight ZHR-8 51146-0600	14000255	Cable for Backlight with JST ZHR-8 and Molex 51146-0600 connectors, 50cm for Panel 17" LVDS Panel G170EG01 V.1AUO (Article 10000132)
cab-LVDS SHDR-40V FI-X30HL, 50cm	14000256	Cable for LVDS with JST SHDR-40V and JAE FI-X30HL connectors, 50cm for Panel 17" LVDS Panel G170EG01 V.1AUO (Article 10000132)
cab-pico-ITX-USB20-Twin	14000210	USB 2.0 internal cable adapter – Twin for conga-JC370
cab-Pico-ITX-SATA-Power	14000205	SATA power cable, for 2.5" HDD only (+5V only), cable length 15cm, for conga-JC370
SATA III cable 30 cm, straight/straight	48000029	SATA III cable, 30 cm with data transfer rate of up to 6 Gbps; Connector: straight/straight, for conga-JC370
cab-DSUB9M-PB9	14000252	RS232/422/485 internal Male Cable Adapter, 15cm, for conga-JC370
cab-Pico-ITX-RS232	14000152	RS232 internal 5-wire Cable Adapter, DSUB9 Male, 15cm, for conga-JC370
cab-PicoITX-GPIO Cable	14000151	GPIO Cable, open end, 15 cm for conga-JC370
cab-Pico-ITX-Buttons-LED	14000147	Internal Buttons and LEDs Cable, 15cm, for conga-JC370
cab-ThinMini-ITX-eLVDS, 1:1	14000129	LVDS cable, configuration 1:1, micro-coax, length = 300 mm, for conga-JC370

*All data is for information purposes only. Although all the information contained within this document is carefully checked, no guarantee of correctness is implied or expressed. Product names, logos, brands, and other trademarks featured or referred are the property of their respective trademark holders. These trademark holders are not affiliated with congatec GmbH. Rev. 2022 Feb\_04*