

## Type 2 surge protection device - VAL-MS 600DC-PV/2+V - 2800642

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Surge arrester for 2-pos. isolated 600 V DC voltage systems, for DIN rail mounting, 3-pos. base element, three plug-in temperature-monitored protective elements, status message on each plug.

### Product Features

- ✓ Increased safety, thanks to compliance with standard EN 50539-11
- ✓ Reliable contact, thanks to integrated rotating latch
- ✓ Easy replacement, thanks to plug-in arresters
- ✓ Optimum inverter protection, thanks to low protection level
- ✓ Efficient replacement of defective plugs, thanks to visual status indicator
- ✓ Optimized maintenance planning, thanks to remote signaling
- ✓ Protection against mismatching, thanks to keyed plugs and base elements
- ✓ Always the right arrester, thanks to universal type 1/type 2 protective components



### Key commercial data

Packing unit	1 pc
Weight per Piece (excluding packing)	320.0 GRM
Custom tariff number	85363010
Country of origin	Germany

### Technical data

#### Dimensions

Height	99 mm
Width	53.4 mm
Depth	65.5 mm
Horizontal pitch	3 Div.

## Type 2 surge protection device - VAL-MS 600DC-PV/2+V - 2800642

### Technical data

#### Ambient conditions

Degree of protection	IP20
Ambient temperature (operation)	-40 °C ... 80 °C
Altitude	≤ 2000 m
Permissible humidity (operation)	5 % ... 95 %

#### General

Standards/specifications	EN 50539-11
IEC test classification	PV T2
SPD failure behavior	OCM
Mounting type	DIN rail: 35 mm
Housing material	PBT / PA
Pollution degree	2
Inflammability class according to UL 94	V0
Surge protection fault message	Optical

#### Protective circuit DC voltage side (DC)

Maximum continuous operating voltage $U_{CPV}$	800 V DC
Open circuit voltage $U_{OCSTC}$	≤ 670 V DC
Short-circuit current rating $I_{SCPV}$	300 A
Rated load current $I_L$	80 A DC
Residual current $I_{PE}$	≤ 20 μA (DC) ≤ 300 μA (AC)
Standby power consumption $P_C$	≤ 20 mVA
Nominal discharge current (8/20) μs	15 kA
Maximum discharge current $I_{max}$ (8/20) μs	40 kA
Total discharge current $I_{Total}$ (8/20) μs	40 kA
Voltage protection level $U_p$ (L+) - (L-)	≤ 2.7 kV
Voltage protection level $U_p$ (L+/L-) - PE	≤ 2.7 kV
Response time $t_A$	≤ 25 ns
Max. required backup fuse with branch wiring	Not required

#### Connection data

Connection method	Screw connection
Conductor cross section stranded min.	1.5 mm <sup>2</sup>
Conductor cross section stranded max.	25 mm <sup>2</sup>
Conductor cross section solid min.	1.5 mm <sup>2</sup>
Conductor cross section solid max.	35 mm <sup>2</sup>
Screw thread	M5

## Type 2 surge protection device - VAL-MS 600DC-PV/2+V - 2800642

### Technical data

#### Connection data

Tightening torque	4.5 Nm
Stripping length	16 mm
Connection method	Biconnect terminal blocks
Conductor cross section stranded min.	1.5 mm <sup>2</sup>
Conductor cross section stranded max.	16 mm <sup>2</sup>
Screw thread	M6
Tightening torque	30 lb <sub>F</sub> -in.

### Classifications

#### eCl@ss

eCl@ss 4.0	27140201
eCl@ss 4.1	27130801
eCl@ss 5.0	27130801
eCl@ss 5.1	27130801
eCl@ss 6.0	27130805
eCl@ss 7.0	27130805
eCl@ss 8.0	27130805

#### ETIM

ETIM 3.0	EC000941
ETIM 4.0	EC000941
ETIM 5.0	EC000941

#### UNSPSC

UNSPSC 6.01	30212010
UNSPSC 7.0901	39121610
UNSPSC 11	39121610
UNSPSC 12.01	39121610
UNSPSC 13.2	39121620

### Approvals

#### Approvals

---

#### Approvals

UL Recognized / KEMA-KEUR / cUL Recognized / cULus Recognized

---

# Type 2 surge protection device - VAL-MS 600DC-PV/2+V - 2800642

## Approvals


Ex Approvals

---

Approvals submitted

---

## Approval details



## Drawings

Circuit diagram

