



FIBER #	COLOR
1	DUMMY
2	ORANGE
3	GREEN
4	DUMMY

TRACE NUMBER { TYCO ELECTRONICS XXXXXXXXXX }
 TYCO ELECTRONICS P/N { 1938250-1 }

$\triangle 6$ LABEL DETAIL

- MAX INSERTION LOSS: 1.0 dB (1310nm)
- $\triangle 2$ PART SHIPPED WITH PIECE OF TAPE TO HOLD FIBER BUFFERS IN PLACE. TAPE TO BE REMOVED AFTER TERMINATING BUFFERED FIBER END OF ASSEMBLY.
- PRODUCT AND PROCESSING MUST MEET REQUIREMENTS OF TYCO ELECTRONICS STANDARD 230-702.

LIGHTRAY MPX CONNECTOR FIBER PATH

1.000±0.051 [39.37±2.00]	1938250-1
L METERS [INCHES]	PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN	J.W.DAVIS	02OCT07	Tyco Electronics Corporation Harrisburg, PA 17105-3608
DIMENSIONS: METERS [INCHES]		CHK	J.BARRY	02OCT07	
MATERIAL		APVD	J.BARRY	02OCT07	
TOLERANCES UNLESS OTHERWISE SPECIFIED:		NAME		PRODUCT SPEC	
0 PLC	± -	NAME		PIGTAIL, FIBER OPTIC, 2 FIBER SINGLEMODE BUFFERED FIBER, LIGHTRAY MPX W/PINS	
1 PLC	± -	APPLICATION SPEC		-	
2 PLC	± -	SIZE	A2	CAGE CODE	00779
3 PLC	± -	DRAWING NO	C-1938250		RESTRICTED TO
4 PLC	± -	WEIGHT	-	SCALE	NTS
ANGLES	± -	CUSTOMER DRAWING	SHEET 1 OF 1		REV A