

NTE952 Integrated Circuit Precision 2.5V Shunt

Description:

The NTE952 integrated circuit is a precision 2.5V shunt regulator diode. This monolithic IC voltage reference operates as a low temperature coefficient 2.5V zener with 0.2Ω dynamic impedance. This device is rated for operation over a 0° to +70°C temperature range and is available in a TO-92 package.

Features:

- Low Temperature Coefficient
- Wide Operating Current of 300μA to 10mA
- 0.2Ω Dynamic Impedance
- ±1% Initial Tolerance Available
- Guaranteed Temperature Stability
- Easily Trimmed for Minimum Temperature Drift
- Fast Turn-On

Absolute Maximum Ratings:

Reverse Current, I_R 15mA
 Forward Current, I_F 10mA
 Operating Temperature Range, T_{opr} 0° to +70°C
 Storage Temperature Range, T_{stg} -60° to +150°C
 Lead Temperature (During Soldering, 10sec), T_L +300°C

Electrical Characteristics: (0° ≤ T_A ≤ +70°C, Note 1 unless otherwise specified)

Parameter	Test Conditions	Min	Typ	Max	Unit
Reverse Breakdown Voltage	T _A = +25°C, I _R = 1mA	2.390	2.490	2.590	V
Reverse Breakdown Change with Current	T _A = +25°C, 400μA ≤ I _R ≤ 10mA	-	2.6	10	mV
Reverse Dynamic Impedance	T _A = 25°C, I _R = 1mA	-	0.2	1	Ω
Temperature Stability	V _R Adjusted to 2.490V, I _R = 1mA	-	1.8	6	mV
Reverse Breakdown Change with Current	400μA ≤ I _R ≤ 10mA	-	3	12	mV
Reverse Dynamic Impedance	I _R = 1mA	-	0.4	1.4	Ω
Long Term Stability	T _A = +25°C ±0.1°C, I _R = 1mA	-	-	20	ppm

Note 1 Unless otherwise specified the NTE952 is specified from 0°C ≤ T_A ≤ +70°C. The maximum junction temperature is 100°C. For elevated junction temperature the derating is based on 180°C/W junction to ambient with 0.4" leads from a PC board and 160°C/W junction to ambient with 0.125" lead length to a PC board.

