

## **Network Infrastructure Solutions**

A. Featured Products

B. Copper Systems

C. Fiber Systems

D. Faceplates, Frames & Surface Mount Boxes

> E. Industrial Networks

F. Audio Video Systems

G. Keystone Cabling Systems

H. Zone Cabling

J. Cable Routing Systems

K. Surface Raceway

L. Cabinets & Rack Systems

M. Power Management

N. Grounding & Bonding

0. Identification Products

P. Cable Management Accessories

> Q. Part Number Index

## ( € Ultra-Cinch™ Hook & Loop Cable Ties

- Unique material with hooks and loops on same side allows user to secure a greater range of bundle diameters, including smaller bundles
- Soft, premium material is safe to use on high performance cabling, protecting against over-tensioning
- Adjustable, releasable, and re-usable ideal for applications requiring frequent moves, adds, or changes
- Low profile contoured cinch ring provides extra strength and bundle tightness while reducing overall bundle size
- Grommet (UGCTC and UGCTE styles) offers strength

and assures reliable installations that resist pullout when bundling and mounting cables within cabinet applications

- Tapered tip facilitates easy, snag-free threading to speed installation
- Use flat head screws for grommet applications shown below
- · A full range of colors
- Operating temperature range: 0°F 140°F (-18°C – 60°C)

Max.

Min. Loop



	Length		Width		Bundle Dia.		Tensile Str.*		Pkg.	Ctn.	
Part Number	In.	m	ln.	mm	In.	mm	Lbs.	N	Qty.	Qty.	
Cinch Ties											
UCT3S-X0	12.00	305.0	0.85	21.6	3.00	76.0	50	222	10	100	
UCT5S-X0	18.00	457.0			5.00	127.0					
Cinch Ties with Brass Grommet											
UGCTC3S-X0	12.00	305.0	0.85	21.6	3.00	76.0	50	222	10	100	
UGCTC5S-X0	18.00	457.0			5.00	127.0					
UGCTE3S-X0	12.00	305.0			3.00	76.0					

Note: 1/4" (6mm) diameter mounting hole on grommet style cinch ties. For color options, reference Hook & Loop cable ties chart, see page P.5.

475.0

\*Note: Minimum 2" overlap required to achieve loop tensile rating.

18.70

## **Cable Bundle Organizing Tool**

Reduces cable installation time compared to traditional methods

**UGCTE5S-X0** 

- Arranges 24 cables prior to applying Panduit® Tak-Ty® Hook & Loop Cable Ties
- Optimizes bundle size and improves installed appearance
- Two inserts handle multiple network cable diameters

127.0

- Ergonomic fit and compact design
- Impact resistant material and low friction design to glide smoothly across cable bundle



		Insert	Ca Diamete	Std. Pkg.	Std. Ctn.	
Part Number	Description	Color	In.	mm	Qty.	Qty.
СВОТ24К	Kit contains jacket cover with hook and loop fastener and two inserts.	Fluorescent Green	0.18 - 0.25	4.6 – 6.3	4	10
		Fluorescent Yellow	0.23 - 0.31	5.8 – 7.9		

