0.25 METER LENGTH



Connector A 132246 SMA Jack Right Angle Bulkhead - Rear Mount Brass Gold + Heatshrink 50 Ohm RG-58 Continuity/Hi-Pot Connector B 112202 BNC Jack Straight Bulkhead - Rear Mount Brass Nickel + Heatshrink

Assembly & Label Notes

Assembly label to be placed ~ 2" from end of connector A and/ or heat shrink Assembly shall be built with SN96.5 LEAD FREE solder. See Routing Notes for additional assembly & testing instructions.

| Right Angle | | Connector A | | | Cable | | Connector B | | |
|--|-------------------|-----------------------|---|---|-------------------|-------------------|-----------------------------|--|--|
| 900 | Part #: | 132246 | | Part #: RG-58 | | Part #: | Part #: 112202 | | |
| 135" | Description: | SMA R/A BHD Jł | KRG58 LMR195 500 | Description: | RG-58 - PE 0.196 | Description: | BNC BHD JK RG58 LMR195 500 | | |
| | Type: | SMA | | Dielectric: | PE | Type: | BNC | | |
| 30° | Gender: | Jack | | Shielding: | Braid | Gender: | Jack | | |
| | Body Type: | Right Angle | | Diameter: | 0.196 | Body Type: | Straight | | |
| 225" | Contact Type: | Solder | | Impedance: | 50 Ohm | Contact Type: | Crimp | | |
| 223 | Polarity: | Standard | | Sheathing: | None | Polarity: | Standard | | |
| | Impedance: | 50 Ohm | | Testing: | Continuity Hi-Pot | Impedance: | 50 Ohm | | |
| | Mounting: | Bulkhead - Rear Mount | | Length: | 0.25 Meter | Mounting: | Bulkhead - Rear Mount | | |
| | Body Material: | Brass | | - | | Body Material: | Brass | | |
| | Body Finish: | Gold | | | | Body Finish: | Nickel | | |
| | IP Rating: | None | | | | IP Rating: | None | | |
| D-Flat | Contact Material: | Beryllium Copper | | | | Contact Material: | Phosphor Bronze Gold | | |
| Bulkhead | Contact Finish: | Gold | | | | Contact Finish: | | | |
| | Max. Freg.: | 12.4 GHz | | | | Max. Freq.: | 4 GHz | | |
| | Booting: | SMA Jack Right Angle | | | | Booting: | BNC Jack Straight BHD 0° | | |
| | Ū | | | | | Clocking: | | | |
| Imphenol PROPRIETARY IN USTOM CABLE FOR ANY PURPOS IN ANY PORT OF ANY PURPOS IN ANY PORT WIT CONTROL LED DOCLIMENT DO NOT CODY | | | | ING MAY CONTAIN PATENTED OR RY INFORMATION AND MUST NOT BE USED SMA-RA-JK/BNC-ST-JK RG58 0.25M | | | | UNLESS SPECIFIED TOLERANCE: | |
| | | | FOR ANY PURPOSE DETRIM INC. IT MAY NOT BE REPRO IN ANY FORM WITHOUT TH | ENTAL TO CUSTOM CA DUCED OR TRANSCRIB | BLE ED | | | 0-18 inches +/- 1/2" over 18" +/- 2% ASSEMBLY: | |
| | | | CUSTOM CABLE INC. ACCEPTANCE OF THIS DRAWING ESTABLISHES AND AGREEMENT OF THE FOREGOING. | | ING Part No: | | | CENTER LABEL IF LENG IS LESS THAN 12 INCHE | |



RoHS 2015/863 Compliance Statement

According to the manufacture of all the component parts contained in this assembly, this product has been determined to be RoHS Compliant with RoHS Directive 2011/65/EU and as amended by Directive 2015/863, and without material exceptions (RoHS3 Complaint).

For the individual component RoHS certificates used in this assembly, please contact Amphenol Custom Cable.

The RoHS Compliance of any product so designated is based upon evidence from the producer (manufacturers') that the component parts comply with the RoHS Directive. Amphenol Custom Cable has taken all reasonable steps to confirm that the OEM (Manufacturer) of the components used in this assembly have provided evidence regarding the absence of the restricted substances to support the manufacturer's claim of compliance.

To the best of our knowledge and with due diligence, we certify that the product listed herein complies with the RoHS requirements.

Date: 10/3/2023

Part Number: Q-2R0080008.25M

Manufacturer: Amphenol Custom Cable

Description: SMA-RA-JK/BNC-ST-JK RG58 0.25M

This information is valid as of the date indicated for the item (part number) listed.

Director of Quality Assurance

Janice Frank