



- NOTES:
1. LOCKING SYSTEM: SCREW
WIRE GAUGE: 0.75mm²
CABLE OUTLET: 6 - 8mm
 2. ELECTRICAL DATA:
CURRENT RATING: 4A
VOLTAGE RATING: 250V
MATING CYCLES: > 100
 3. MECHANICAL:
OPERATING TEMP.: -40°C - 85°C
PROTECTION CLASS: IP67
 4. MATERIAL:
CONTACT: CuZn (BRASS)
CONTACT PLATING: Au (GOLD)
CONTACT BODY: PA
HOUSING: ZINC DIE CAST, NICKEL

ENG.-NO: E1AS01-32

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION											
EC DESCRIPTION EC NO: 108741 DRWN: THAERDT CHK'D: A2	2016/09/23	RSILLER	2016/09/23	QUALITY SYMBOLS	GENERAL TOLERANCES (UNLESS SPECIFIED)	DIMENSION UNITS	SCALE				
				▽ = 0		MM	2:1				
				▽ = 0		DRWN BY	DATE				
				▽ = 0		MSCHWARZ	2015/07/06				
				▽ = 0	ANGULAR TOL ± 1.0 °	CHK'D BY	DATE	FA M12 ETH 4P DC FE RA SCR SHLD			
				▽ = 0	4 PLACES ±	APPR BY	DATE	PRODUCT CUSTOMER DRAWING			
				▽ = 0	3 PLACES ±	DRAWING SIZE	THIRD ANGLE PROJECTION	SERIES	MATERIAL NUMBER	CUSTOMER	
				▽ = 0	2 PLACES ± 0.05	A3		130047	1300470038	GENERAL MARKET	
				▽ = 0	1 PLACE ± 0.3			DOCUMENT NUMBER	DOC TYPE	DOC PART	SHEET NUMBER
				▽ = 0	0 PLACES ± 0.5			1300470038	PSD	000	1 OF 1
				▽ = 0	DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS						