

DASH


APRVD: DMR

PROPRIETARY OF GLOBTEK, INC. ANY REPRODUCTION, DISCLOSURE OR

PROPRIETARY INFORMATION:

REV

PACKING: **HANKING**




REV.

SCALE: NONE

PART NO

DATE:

03/23/09



Complies with Requirements of California

REVISION

B'

APPROVED

NOTES

SHEET 1/1

03/23/09

DESCRIPTION

GENERAL SPECIFICATIONS:

RATING: 10A / 125V AC

CABLE TYPE / SIZE: SVT. 18 AWG X 3. SHIELDED

TEMPERATURE RATING: 60° C MIN.

CONDUCTOR COLORS: BLACK / WHITE / GREEN

CABLE JACKET COLOR: **BLACK**

OVERALL LENGTH (L): 2000 + 20 mm CABLE OUTER DIAMETER: 6.8 + 0.1mm END 'A' TERMINATION: **NEMA 5-15P** END 'B' TERMINATION: **CUT BLUNT** APPROVALS PLUG: UL. CSA

APPROVALS CABLE: UL, CSA OR cUL APPROVALS CONNECTOR: UL. CSA OR cUL

NOTES:

Contents of this document

prior notice

are subject to change withou

1. CORD. PLUG AND CONNECTOR MUST BE MARKED WITH APPROVAL SYMBOLS OR FILE NUMBER(S).





Globtek Inc. will not be liable for the

safety and performance of these power

product if unauthorized access and repair

ble UL,CSA or EN Standards for proper

installation instruction.



Globtek product are not authorized for use as mission critical components in life support, hazardous environment, nuclear or aircraft applications without prior written occurs. End user should consult the applicaapproval from the CEO of Globtek Inc.

TABULATION BLOCK TOLERANCES: 🕟 GlobTek,̈ Inc. DECIMALS ANGULAR 186 Veterans Dr. Northvale, NJ 07647 $xx + /_{-} 0.1$ Tel. 201-784-1000 Fax 201.784.0111 www.globtek.com .xxx +/- .005 MILLIMETERS ANGULAR DATE: DWG TITLE: NORTH AMERICAN DETACHABLE CORDSET INIT.BY: GC .xx +/- 0.3 03/23/09 xxx +/= 013 DATE: FSCN No.: SIZE REV. DRAWN: NF MODEL: N/AG, CC Α Α 03/23/09

PART NO: 3021876F700(R)

DESCRIPTION