



NOTES: UNLESS OTHERWISE SPECIFIED.

1. MATERIALS & FINISH:

- 1.1 HOUSINGS & NUT: PASSIVATED STAINLESS STEEL.
- 1.2 CENTER CONTACT: GOLD PLATED BERYLLIUM COPPER.
- 1.3 DIELECTRIC: PTFE (TEFLON).
- 1.4 SUPPORT BEAD: NORYL
- 1.5 GASKET: SILICONE RUBBER
- 1.6 RETAINING RINGS: UNPLATED BERYLLIUM COPPER

2. ELECTRICAL SPECIFICATION:

- 2.1 FREQUENCY RANGE: DC TO 18.0 GHz
- 2.2 VSWR (MAX)
  - DC TO 4.0 GHz: 1.04:1
  - 4.0 TO 8.0 GHz: 1.07:1
  - 8.0 TO 18.0 GHz: 1.12:1
- 2.3 IMPEDANCE: 50 OHMS

<p>This PROPRIETARY Document is property of Cinch Connectivity Solutions. It is confidential in nature, non-transferable, and issued with the clear understanding that it is not traded or copied without permission and is returnable upon demand.</p> <p>INTERPRET DRAWING IN ACCORDANCE WITH ASME Y14.5-2009.</p>	3RD ANGLE PROJECTION 	<b>MIDWEST MICROWAVE</b>		
	RoHS2 <input checked="" type="checkbox"/> 2011/65/EU	Title: ADAPTER N JACK/3.5MM PLUG		Model No. ADT-2714-NF-3MM-02-01
UNLESS OTHERWISE SPECIFIED UNITS: INCH .XX ±.02 .XXX ±.005 ANGLES ±2°		Size A	DO NOT SCALE DRAWING	Date: 11/5/2014
			Sheet 1 of 1	