


JKL LAMP PART NUMBER	COLOR	STARTING CIRCUIT VOLTAGE VS (Vrms)	OPERATING LAMP VOLTAGE VL (Vrms)	OPERATING LAMP CURRENT IL (mA rms)	BRIGHTNESS (CANDELA/m ²)	*RATED LIFE (HRS)
BF325-22B	LCD HIGH OUTPUT WHITE 7400°k RGB	400 @ 25°C	165	5	19,000 ± 10%	7,500

* RATED LIFE IS DEFINED AS THE POINT AT WHICH THE INTENSITY BECOMES 50% OF THE INITIAL RATING.

			METRIC  THIRD ANGLE PROJECTION		DIMENSIONS ARE IN MILLIMETERS TOLERANCE UNLESS OTHERWISE SPECIFIED 1 PL +/- 0 2 PL +/- 0 ANGLE +/- 0		JKL COMPONENTS CORPORATION				
					TITLE MINIATURE COLD CATHODE FLUORESCENT LAMP						
B	26±2 TO 17±2 - DRAW. TO CAD	8/1/01	DRAWN BY	APPV'D BY	DATE	SIZE	FSCM NO.	DRAWING NO.			
A	25±1 TO 25±2-17±2 TO 26±2	5/15/98	L. WENGSTROM	F.D.	8/2/01	A	55335	BF325-22B			
	RELEASED	9/12/97	- CAD DRAWING -			SCALE	RELEASED DATE	REVISION DATE	REV. NO.	SHEET	
REV. NO.	DESCRIPTION/ECO NUMBER	APPV'D DATE	MANUAL REVISIONS NOT PERMITTED			NONE	9/12/97	8/1/01	B	1 OF 1	