





7.62 mm Terminal Blocks



LP 7.62/90
Single-Level
90° Orientation
Without Test Points





LPP 7.62/90
Single-Level
90° Orientation
With Test Points





LP 7.62/135
Single-Level
135° Orientation
With Test Points



TOP 4GS/7.62/90
Single-Level
90° Orientation
Without Test Points



TOP 4GS/7.62/180
Single-Level
180° Orientation
Without Test Points



Technical Data											
UL	CSA*	VDE		UL	CSA*	VDE		UL	CSA*	VDE	
Rated Voltage	300 V	300 V	400 V	300 V	300 V	400 V		300 V	300 V	400 V	
Rated Current	10 A	10 A	26 A	10 A	10 A	26 A		10 A	10 A	26 A	
Wire Size	#26...12 AWG	#26...12 AWG	2.5 mm²	#26...12 AWG	#26...12 AWG	2.5 mm²		#26...12 AWG	#26...12 AWG	2.5 mm²	
Strip Length	7 mm	7 mm	7 mm	7 mm	7 mm	7 mm		7 mm	7 mm	7 mm	
Torque Nm (lb. in.)	0.5 (4.4)	0.5 (4.4)	0.5 (4.4)	0.5 (4.4)	0.5 (4.4)	0.5 (4.4)		0.5 (4.4)	0.5 (4.4)	0.5 (4.4)	
Pin Length	4.5 mm	4.5 mm	4.5 mm	4.5 mm	4.5 mm	4.5 mm		4.5 mm	4.5 mm	4.5 mm	
Poles	Type	Part No. orange	black	Poles	Type	Part No. orange	black	Poles	Type	Part No. orange	black
2	LP 7.62/90/2	159466	169720	2	LPP 7.62/90/2	159468	169724	2	LP 7.62/135/2	159580	169728
3	LP 7.62/90/3	159467	169721	3	LPP 7.62/90/3	159469	169725	3	LP 7.62/135/3	159581	169729
4	LP 7.62/90/4	995336	995349	4	LPP 7.62/90/4	995362	995375	4	LP 7.62/135/4	995388	995401
5	LP 7.62/90/5	995337	995350	5	LPP 7.62/90/5	995363	995376	5	LP 7.62/135/5	995389	995402
6	LP 7.62/90/6	995338	995351	6	LPP 7.62/90/6	995364	995377	6	LP 7.62/135/6	995390	995403
7	LP 7.62/90/7	995339	995352	7	LPP 7.62/90/7	995365	995378	7	LP 7.62/135/7	995391	995404
8	LP 7.62/90/8	995340	995353	8	LPP 7.62/90/8	995366	995379	8	LP 7.62/135/8	995392	995405
9	LP 7.62/90/9	995341	995354	9	LPP 7.62/90/9	995367	995380	9	LP 7.62/135/9	995393	995406
10	LP 7.62/90/10	995342	995355	10	LPP 7.62/90/10	995368	995381	10	LP 7.62/135/10	995394	995407
11	LP 7.62/90/11	995343	995356	11	LPP 7.62/90/11	995369	995382	11	LP 7.62/135/11	995395	995408
12	LP 7.62/90/12	995344	995357	12	LPP 7.62/90/12	995370	995383	12	LP 7.62/135/12	995396	995409
13	LP 7.62/90/13	995345	995358	13	LPP 7.62/90/13	995371	995384	13	LP 7.62/135/13	995397	995410
14	LP 7.62/90/14	995346	995359	14	LPP 7.62/90/14	995372	995385	14	LP 7.62/135/14	995398	995411
15	LP 7.62/90/15	995347	995360	15	LPP 7.62/90/15	995373	995386	15	LP 7.62/135/15	995399	995412
16	LP 7.62/90/16	995348	995361	16	LPP 7.62/90/16	995374	995387	16	LP 7.62/135/16	995400	995413

Technical Data	UL	CSA	VDE	UL	CSA	VDE	
Rated Voltage	300 V	600 V	250 V	300 V	600 V	250 V	
Rated Current	25 A	25 A	36 A	25 A	25 A	36 A	
Wire Size	#22...10 AWG	#26...10 AWG	4 mm²	#22...10 AWG	#26...10 AWG	4 mm²	
Strip Length	13 mm	13 mm	13 mm	13 mm	13 mm	13 mm	
Torque Nm (lb. in.)	0.5 (4.4)	0.5 (4.4)	0.5 (4.4)	0.5 (4.4)	0.5 (4.4)	0.5 (4.4)	
Pin Length	3.5 mm	3.5 mm	3.5 mm	3.5 mm	3.5 mm	3.5 mm	
Poles	Type	Part No.		Poles	Type	Part No.	
1*	TOP 4GS/7.62/90/1 OG	28816		1*	TOP 4GS/7.62/180/1 OG	28916	
2	TOP 4GS/7.62/90/2 OG	28966		2	TOP 4GS/7.62/180/2 OG	29836	
3	TOP 4GS/7.62/90/3 OG	28976		3	TOP 4GS/7.62/180/3 OG	29846	
4	TOP 4GS/7.62/90/4 OG	29016		4	TOP 4GS/7.62/180/4 OG	29856	
5	TOP 4GS/7.62/90/5 OG	995434		5	TOP 4GS/7.62/180/5 OG	995442	
6	TOP 4GS/7.62/90/6 OG	995435		6	TOP 4GS/7.62/180/6 OG	995443	
7	TOP 4GS/7.62/90/7 OG	995436		7	TOP 4GS/7.62/180/7 OG	995444	
8	TOP 4GS/7.62/90/8 OG	995437		8	TOP 4GS/7.62/180/8 OG	995445	
9	TOP 4GS/7.62/90/9 OG	995438		9	TOP 4GS/7.62/180/9 OG	995446	
10	TOP 4GS/7.62/90/10 OG	995439		10	TOP 4GS/7.62/180/10 OG	995447	
11	TOP 4GS/7.62/90/11 OG	995440		11	TOP 4GS/7.62/180/11 OG	995448	
12	TOP 4GS/7.62/90/12 OG	995441		12	TOP 4GS/7.62/180/12 OG	995449	