





CKT SIZE	DIMENSION				
	A	B	C	D	E
4	2.00	4.85	6.65	5.00	---
6	4.00	6.85	8.65	7.00	---
8	6.00	8.85	10.65	9.00	---
10	8.00	10.85	12.65	11.00	---
12	10.00	12.85	14.65	13.00	---
14	12.00	14.85	16.65	15.00	8.00
16	14.00	16.85	18.65	17.00	10.00
18	16.00	18.85	20.65	19.00	12.00
20	18.00	20.85	22.65	21.00	14.00
22	20.00	22.85	24.65	23.00	16.00
24	22.00	24.85	26.65	25.00	18.00
26	24.00	26.85	28.65	27.00	20.00
28	26.00	28.85	30.65	29.00	22.00
30	28.00	30.85	32.65	31.00	24.00
32	30.00	32.85	34.65	33.00	26.00
34	32.00	34.85	36.65	35.00	28.00
36	34.00	36.85	38.65	37.00	30.00
38	36.00	38.85	40.65	39.00	32.00
40	38.00	40.85	42.65	41.00	34.00
42	40.00	42.85	44.65	43.00	36.00
44	42.00	44.85	46.65	45.00	38.00
46	44.00	46.85	48.65	47.00	40.00
48	46.00	48.85	50.65	49.00	42.00
50	48.00	50.85	52.65	51.00	44.00



- NOTES:
- FOR ILLUSTRATION PURPOSES, 20 CIRCUIT SIZE WAFER IS SHOWN.
 - MATERIAL :
HOUSING : LCP, UL94V-0, GLOW WIRE CAPABLE PER IEC-60335-1 5TH EDITION, GLASS FILLED. COLOR: BLACK.
PIN : 0.50MM SQ. COPPER ALLOY.
 - PRODUCT SPECIFICATION PS-151117-0001 APPLIES.
 - RIB LOCATION VARIES, DEPENDING ON CKT SIZES.
 - CKT 4 AND 6 HAS NO IDENTIFICATION TAG.
 - GAUGING AT SOLDER TAIL.
 - REFER TO PACKAGING SPECIFICATION
FOR TUBE : PK-151117-0001
FOR TAPE & REEL : PK-151117-3000
 - CAVITY ID AND MX LOGO SHALL BE LOCATED APPROXIMATELY AS SHOWN.

- NOTE CONTINUE.
- POSITION OF CAP TO BE LOCATED AT CENTER OF DIM A, IRREGARDLESS OF CKT SIZES. TOP SURFACE OF CAP TO BE FLAT FOR PICK & PLACE PURPOSE.
 - SINGLE LOCK FEATURE FOR CKT 4-12.
 - DUAL LOCKS FEATURE FOR CKT 14 AND ABOVE.
 - DETAIL 1 AND DETAIL 2 FOR MMC REFERENCE ONLY.

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX ELECTRONIC TECHNOLOGIES, LLC AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION		CURRENT REV DESC:		molex	
DIMENSION UNITS	SCALE	EC NO: 619055			
mm	NTS	DRWN: HK02 2019/05/13		MGRID, SHROUDED HEADER THROUGH HOLE	
GENERAL TOLERANCES (UNLESS SPECIFIED)		CHK'D: NMANE02 2019/07/09		PRODUCT CUSTOMER DRAWING	
4 PLACES	±	APPR: MRAMAKRISHNA 2019/07/09		DOCUMENT NUMBER	
3 PLACES	±	INITIAL REVISION:		DOC TYPE	
2 PLACES	± 0.2	DRWN: ATSEE 2014/10/09		DOC PART	
1 PLACE	±	APPR: KHLIM 2015/06/18		REVISION	
0 PLACES	±	ANGULAR TOL ± 3.0°		SD-151117-0001	
DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		THIRD ANGLE PROJECTION	DRAWING	SERIES	MATERIAL NUMBER
			A3-SIZE	151117	CUSTOMER
					GENERAL MARKET
					SHEET NUMBER
					1 OF 3

BOARD TO BOARD (BTB) DISTANCE

HEADER	MATES WITH (RECEPTACLE)	BTB DISTANCE	PICTORIAL VIEW
151117	78787	6.94	
	78788	7.15	
	79107	6.94	
	79109	7.15	

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX ELECTRONIC TECHNOLOGIES, LLC AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION													
DIMENSION UNITS		SCALE		CURRENT REV DESC:									
mm		NTS											
GENERAL TOLERANCES (UNLESS SPECIFIED)				EC NO: 619055				ASSEMBLY					
				DRWN: HK02 2019/05/13				MGRID, SHROUDED HEADER THROUGH HOLE					
				CHK'D: NMANE02 2019/07/09				PRODUCT CUSTOMER DRAWING					
				APPR: MRAMAKRISHNA 2019/07/09									
				INITIAL REVISION:				DOCUMENT NUMBER					
				DRWN: DRWN BY XXXX/XX/XX				SD-151117-0001		DOC TYPE		DOC PART	
				APPR: APPR BY XXXX/XX/XX				PSD		001		A3	
ANGULAR TOL ± 3.0°				THIRD ANGLE PROJECTION				DRAWING		SERIES		MATERIAL NUMBER	
DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS								A3-SIZE		151117		CUSTOMER	
								GENERAL MARKET				SHEET NUMBER	
												3 OF 3	