



ISO9001:2008 Certified

**Mechanical Specifications (mm)**

	D:	17.0	± max
	T:	8.0	± max
	Lead Diameter	1.0	± nom
	S:	7.8	± nom
	L:	38.0	± nom
	Coating Lead Run Down (straight Leads)	4.0	± max
	B:	4.00	± nom
	C:	6.00	± nom



**Electrical Specifications**

	Resistance:	40.0 Ω	± 25 %
	Max Steady State Current upto 65°C:	4.10	A
	Max Rec. Energy Rating:	135	J
	Actual Failure Instantaneous Energy:	270	J
	Maximum Capacitance @ 120 VAC:	9,300	µf
	Maximum Capacitance @ 240 VAC:	2,344	µf
	Maximum Capacitance @ 440 VAC:	541	µf
	Maximum Capacitance @ 680 VAC:	270	µf
	Resistance @ 100% Max Current:	0.28	Ω
	Resistance @ 50% Max Current:	0.95	Ω
	Body Temperature at 100% Max Current:	154.00	°c
	Dissipation Constant:	49.4	mw/°c
	Thermal Time Constant:	114	Sec.
	Material Type (for Beta and Curve):	I	

<b>MS15 40004</b>	
Date: 02/05/2009	Drawn by: Erin Landis
Ametherm, Inc. 3111 N. Deer Run Road Carson City, Nevada USA 89701 www.ametherm.com	Approved By: Mehdi Samii
	Revision: a