

ADAM-3617-AE ADAM-3624-AE

NEW



ADAM-3617-AE



Specifications

General

- Power Consumption 1W (Max)
- Certification CE/FCC

Analog Input

- Channels 4, differential
- Input Type Voltage, Current
- Resolution 16-bit
- Voltage/Current $\pm 10V$, $\pm 2.5V$, 0 ~ 20mA, Range 4 ~ 20mA
- Sampling rate 10 sample/second (total)
- Input Impedance $0.1 M\Omega$
- Accuracy $\pm 0.1\%$ or better of FSR (Voltage) $\pm 0.2\%$ or better of FSR (Current)
- CMR @ 50/60 Hz 90 dBs
- NMR @ 50/60 Hz 60 dBs
- Span Drift $\pm 25 \text{ ppm}/^\circ\text{C}$
- Zero Drift $\pm 6 \mu\text{V}/^\circ\text{C}$, $\pm 6 \mu\text{A}/^\circ\text{C}$
- Isolation Voltage 2000 V_{DC}
- Burn-out detection Yes (Current-only)

Environment

- Operating Temp. -40 ~ 70°C
- Storage Temp. -40 ~ 85°C
- Humidity 5 ~ 95% (no-condensation)

Ordering Information

- ADAM-3617-AE 4-ch Analog Input Module

4-ch Analog Input Module

4-ch Analog Output Module

NEW



ADAM-3624-AE



Specifications

General

- Power Consumption 1W (Max)
- Certification CE/FCC

Analog Output

- Channels 4
- Output Impedance 4Ω
- Output Settling Time $10 \mu\text{s}$
- Driving Load Voltage: $2k\Omega$
Current: 500Ω
- Output Type Voltage, Current
- Output Range $0 \sim 10 \text{ V}_\text{DC}$
 $0 \sim 20 \text{ mA}$ $4 \sim 20 \text{ mA}$
- Resolution 12-bit
- Accuracy $\pm 0.3\%$ of FSR (Voltage) at 25°C $\pm 0.3\%$ of FSR (Current) at 25°C
- Current Load Resistor $0 \sim 500\Omega$
- Drift $\pm 25 \text{ ppm}/^\circ\text{C}$
- Isolation Voltage 2000 V_{DC}

Environment

- Operating Temp. -40 ~ 70°C
- Storage Temp. -40 ~ 85°C
- Humidity 5 ~ 95% (no-condensation)

Ordering Information

- ADAM-3624-A 4-ch Analog Output Module