

OTHER OPTION

-TR


= Tape & Reel (-026 & -052 only)

-FR


= Full Reel Tape & Reel (must order max. quantity per reel; contact Samtec for quantity breaks) (-026 & -052 only)

Q2[™] HIGH-SPEED GROUND PLANE CONNECTORS

(0.635 mm) .025" PITCH RIGHT-ANGLE GROUND PLANE HEADERS & SOCKETS



(0.635 mm) .025" PITCH EDGE MOUNT GROUND PLANE HEADERS & SOCKETS



View complete specifications at: samtec.com?QMS-EM or samtec.com?QFS-EM

Q RATE[®] SLIM BODY HIGH-SPEED GROUND PLANE CONNECTORS

(0.80 mm) .0315" PITCH RIGHT-ANGLE SLIM BODY GROUND PLANE HEADERS & SOCKETS

QRM8-RA Board Mates: QRF8 (-GP Required) QRF8-RA Board Mates: QRM8 (-GP Required)	SERIES -	POSITIONS PER ROW	= 01 = PLATING = RA	GP	OPTION
	QRM8 Header QRF8	-026, -052, -078 (52 total positions per bank)	-L = 10 μ" (0.25 μm) Gold contact, Matte Tin on tails	-GP =Guide Post (Requires -GP on mating connector)	−K = (7.00 mm) .275" DIA Polyimide film Pick & Place Pad (–052 only)
	Socket			connectory	– TR =Tape & Reel (–026, –052 only)
					-FR = Full Reel Tape & Reel (must order max. quantity per reel; contact Samtec for quantity breaks) (-026 & -052 only)

Note:

Some lengths, styles and options are non-standard, non-returnable. View complete specifications at: samtec.com?QRM8-RA or samtec.com?QRF8-RA

Unless otherwise approved in writing by Samtec, all parts and components are designed and built according to Samtec's specifications which are subject to change without notice.