



NOTES: Finish (Plating Thickness in Micro-inches)
 1. Brass
 2. Nickel Pl. 100 Min. Thick over Copper Pl. 50 Min. Thick
 3. Phosphor Bronze
 4. Gold Pl. 3 Min Thick over Nickel Pl. 50 Min. Thick over Copper Pl. 50 Min. Thick
 5. DELRIN

RoHS Compliant

1. Max. Panel Thickness = .217 (5.5)

Dimensions are in Inches			
Unless Otherwise Specified			
Tolerances			
0.5-6 = ±0.2			
6-30 = ±0.4			
30-120 = ±0.6			
120-315 = ±1			
315-1000 = ±1.6			
1000-2000 = ±2.4			

7	Hex-Nut	Note 1	Note 2	1	
6	Lock Washer	Note 1	Note 2	1	
5	Lock Ring	Iron	Note 2	1	
4	Contact Pin	Note 3	Note 4	1	
3	Insulator	Note 5	Natural	2	
2	Insulator	Note 5	White	1	
1	Body	Note 1	Note 2	1	
No.	Description	Material	Finish	Q'ty	Drawing No.

Part No.	
Approved	Date 8-27-2015
Checked	Date 8-27-2015
Drawn	Date 8-27-2015

NTE Electronics	
Title	BNC Jack to Jack Bulkhead Isolated Adapter
Drawing No.	06-B012
File No.	