



NOTES:

1. METALSHIELDS: STEEL; 315µin-470µin ZINC; YELLOW CHROMATE
2. INSULATORS: PBT GF UL 94 V-0; BLACK
3. CONTACTS: COPPER ALLOY; PLATING: (SEE PART NO.):
 - PLEASE ADD A for GOLD FLASH over NICKEL (PREFERRED TYPE)
 - PLEASE ADD B for 20µin HARD GOLD over min. 50µin NICKEL
 - PLEASE ADD C for 30µin HARD GOLD over min. 50µin NICKEL
4. THREADED INSERTS: COPPER ALLOY; min. 200µin TIN over 80µin NICKEL
5. COLLARS: COPPER ALLOY; min. 200µin TIN over 80µin NICKEL
6. MAXIMUM TORQUE VALUE FOR THREAD: 6 in.LB
7. CONNECTOR IS PART MARKED: **162□10419X CONEC ABC** (see note 3)

THIS DRAWING MAY NOT BE COPIED OR REPRODUCED IN ANY WAY, AND MAY NOT BE PASSED ON TO A THIRD PARTY WITHOUT WRITTEN PERMISSION. OWNERSHIP AND COPYRIGHT OF CONEC GmbH DO NOT ALTER CAD DRAWING BY HAND				tolerance		scale: 2:1 (5:1)
				date	name	material: SEE NOTES
				drawn	26.03.13	Lehmenkühler
				appd.	27.03.13	Fischer
				norm		
				d-old		
				rev.		
			description			
			date			
			name			
			CONEC [®]		title: D-SUB FEMALE	
					9pos. WIRE WRAP with threaded insert	
			dwg no: Inventor 10		DIN-A3	
			part no: 162□10419X (see note 3)		sh: 1	