



PIN	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40				
COM1		8J	7J	6J	5J	4J	3J	2J	1J	COM1	1A	1H	2A	2H	3A	3H	4A	4H	5A	5H	6A	6H	7A	7H	8A	8H	COM2																	
COM2	8F	8K	7F	7K	6F	6K	5F	5K	4F	4K	3F	3K	2F	2K	1F	1K	COM3																											
COM3	8E	8G2	7E	7G2	6E	6G2	5E	5G2	4E	4G2	3E	3G2	2E	2G2	1E	1G2	COM4																											
COM4	8D	8L	7D	7L	6D	6L	5D	5L	4D	4L	3D	3L	2D	2L	1D	1L	COM4	1D	1M	2D	2M	3D	3M	4D	4M	5D	5M	6D	6M	7D	7M	8D	8M											

NOTES:

- | | |
|-------------------------------------------|-------------------------------|
| 1. DISPLAY TYPE: TN | 5. OPERATING VOLTAGE: 5.0 V |
| 2. VIEWING DIRECTION: 12:00 | 6. OPERATING TEMP: -20°C~80°C |
| 3. POLARIZER MODE: POSITIVE/TRANSFLECTIVE | 7. STORAGE TEMP: -40°C~80°C |
| 4. DRIVER METHOD: 1/4 DUTY 1/3 BIAS | 8. CONNECTOR: PIN |