0.25 METER LENGTH

Connector A 132114RP SMA Plug Straight Brass Gold + Heatshrink 50 Ohm RG-174 Continuity/Hi-Pot Connector B 3FA1ENZRJ-C01Y3 FAKRA Jack Right Angle Zinc Nickel + Heatshrink

Assembly & Label Notes

Assembly label to be placed ~ 2" from end of connector A and/ or heat shrink Assembly shall be built with SN96.5 LEAD FREE solder. See Routing Notes for additional assembly & testing instructions.

Connector A			Cable			Connector B		
Part #:	132114RP		Part #:	RG-174	Part #:	3FA1ENZRJ-C01Y3	}	
Descrip	tion: SMA PLUG RP	SMA PLUG RP RG316 500		RG-174 - PE 0.1	Description:	FAKRA-Z JK RA RG174 RG316 500		
Type:	SMA	SMA		PE	Туре:	FAKRA		
Gender	: Plug	Plug		Braid	Gender:	Jack		
Body Ty	/pe: Straight	Straight		0.1	Body Type:	Right Angle		
Contact	Type: Crimp	Crimp		50 Ohm	Contact Type:	Crimp		
Polarity	Reverse			None	Polarity:	Standard		
Impeda			Testing:	Continuity Hi-Pot	Impedance:	50 Ohm		
Mountir		Cable		0.25 Meter	Mounting:	Cable		
Body M	aterial: Brass	Brass			Body Material:	Zinc		
Body Fi					Body Finish:	Nickel None		
IP Ratin	a: None				IP Rating:			
	•				Contact Material:	Beryllium Copper Gold 3 GHz FAKRA-Z Jack Right Angle 0°		
Contact	, ,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,				Contact Finish:			
Max. Fr	ea.: 12.4 GHz				Max. Freq.:			
Booting	•				Booting:			
					Clocking:			
				KDAZ DA IK C174 0 25M	-RA-JK G174 0.25M UNLESS SPECIFIED TOLERANCE:			
FOR AN		FOR ANY PURPOSE DETRIMENT	PROPRIETARY INFORMATION AND MUST NOT BE USED FOR ANY PURPOSE DETRIMENTAL TO CUSTOM CABLE NC. IT MAY NOT BE REPRODUCED OR TRANSCRIBED		SMA-ST-PL-RP/FKRAZ-RA-JK G174 0.25M		0-18 inches +/- 1/2" over 18" +/- 2%	
CUSTOM CABLE		INC. II MAY NOT BE REPRODUCED OR TRANSCRIBED IN ANY FORM WITHOUT THE WRITTEN CONSENT OF CUSTOM CABLE INC. ACCEPTANCE OF THIS DRAWING ESTABLISHES AND AGREEMENT OF THE FOREGOING.					ASSEMBLY:	
CONTROLLED DOCUMENT - DO NOT COPY					Part No: Q-6805C0003.25M		CENTER LABEL IF LENGTH IS LESS THAN 12 INCHES	