

## Cable - CABLE-KS40/KS40/10M/YUC/CS - 2904433

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Assembled round cable with two molded 40-pos. socket strips (1:1 connection). Cable length: 10.0 m

Illustration shows the 50-pos. version

### Key Commercial Data

|                      |          |
|----------------------|----------|
| Packing unit         | 1 STK    |
| Custom tariff number | 85444290 |
| Country of origin    | SKR      |

### Technical data

#### General

|   |   |
|---|---|
| Nominal voltage $U_N$                         | 30 V DC                                 |
| Max. current carrying capacity per path       | 500 mA (up to 70°C ambient temperature) |
| Max. conductor resistance                     | 0.16 $\Omega$ /m                        |
| Length of cable                               | 10 m                                    |
| Single wire, cross section                    | 0.14 mm <sup>2</sup>                    |
| Single wire, cross section [AWG]              | 26                                      |
| Conductor construction: Number of litz wires: | 7                                       |
| Single wire, material                         | Cu tin-plated                           |
| External diameter                             | 11 mm                                   |
| Shielding                                     | yes                                     |
| Outer sheath, material                        | PVC                                     |
| External sheath, color                        | gray RAL 7035                           |

#### Environmental conditions

|                                 |                  |
|---------------------------------|------------------|
| Ambient temperature (operation) | -20 °C ... 50 °C |
|---------------------------------|------------------|

## Cable - CABLE-KS40/KS40/10M/YUC/CS - 2904433

### Technical data

#### Environmental conditions

|   |                                    |
|---|------------------------------------|
| Ambient temperature (storage/transport) | -20 °C ... 70 °C                   |
| Flame resistance                        | IEC 60332-3-22                     |
| Resistance to oil                       | DIN VDE 0472 Part 803, test type B |
| Gasoline resistance                     | Against occasional splashes        |

#### Connector, module side

|                       |                           |
|-----------------------|---------------------------|
| Connection name       | Field level               |
| Connection method     | Yokogawa, KS compatible   |
| Torque                | 0.5 Nm (Screw connection) |
| Number of connections | 1                         |
| Number of positions   | 40                        |

#### Connector, controller side

|                       |                                |
|-----------------------|--------------------------------|
| Connection name       | Controller level               |
| Connection method     | Yokogawa, I/O cards compatible |
| Torque                | 0.5 Nm (Screw connection)      |
| Number of connections | 1                              |
| Number of positions   | 40                             |

#### Supported controller

|            |                          |
|------------|--------------------------|
| Controller | YOKOGAWA CS3000 CentumVP |
|------------|--------------------------|

#### Standards and Regulations

|                   |                                    |
|-------------------|------------------------------------|
| Resistance to oil | DIN VDE 0472 Part 803, test type B |
| Flame resistance  | IEC 60332-3-22                     |

### Classifications

#### eCl@ss

|            |          |
|------------|----------|
| eCl@ss 4.0 | 27060306 |
| eCl@ss 4.1 | 27060306 |
| eCl@ss 5.0 | 27061801 |
| eCl@ss 6.0 | 27249205 |
| eCl@ss 7.0 | 27249205 |
| eCl@ss 8.0 | 27249205 |
| eCl@ss 9.0 | 27242220 |

#### ETIM

|          |          |
|----------|----------|
| ETIM 2.0 | EC000237 |
| ETIM 3.0 | EC000237 |

## Cable - CABLE-KS40/KS40/10M/YUC/CS - 2904433

### Classifications

#### ETIM

|          |          |
|----------|----------|
| ETIM 4.0 | EC000237 |
| ETIM 5.0 | EC000237 |

#### UNSPSC

|               |          |
|---------------|----------|
| UNSPSC 6.01   | 26121620 |
| UNSPSC 7.0901 | 26121620 |
| UNSPSC 11     | 26121620 |
| UNSPSC 12.01  | 26121620 |
| UNSPSC 13.2   | 26121620 |