





All information contained herein applies only to the above listed part number. Other versions of this part number with electrical or mechanical variations are available. Contact CUI Inc. for further assistance. 9615 SW Allen Blvd., Ste. 103, Beaverton OR 97005  
 800-275-4899 • 503-643-4899 • Fax: 503-643-6129 • www.cui.com

Parts Name	Specification	Q'ty
1. Transformer	EI- 57	1
2. Enclosure	Noryl SE-100	1
3. PCB. Assembly		
PCB.	Phenolic 94V-0,105□	1
Diode	50V 3 A ; 50V 1A	2/1
Capacitor	4700uf 16V 105 □	1
	47uf 25V 105 □	1
Ceramic Capacitor	0.1 uf 50V	2
	0.02uf 50V	2
IC	3522	1
Resistor	100 ohm 1/2W	1
	2.7 ohm 1/2W	1
Current Fuse	5 A 250 V Slow-Blow	1
Ins. Cur. Fuse	PVC Sleeving Tubing 105 300V	1
Heat Sink	Aluminum	1
4. Output Cord	AWG# 18 SPT-1 6 ft min.	1
5. Input Cord	AWG# 18SPT-2 3C 6 ft min.	1
6. Foam	94HF-2 or FR212	1
7. Name Plate	Polyester Film	1



Part Name	Material & Type	Spec or Q'ty
1. Core	Silicon Steel	0.35 mm
2. Bobbin	Polybutylene Terephthalate Valox 420-SEO	0.71mm min.
3. Primary Winding	NEW Thermelt Copper Wire 2NEW	mm
	Polyurethane Enameled Copper Wire	0.27 mm
4. Primary Crossover	Acetate Tape	0.18mmx2PCS
5. Insulation Between Primary Lead Winding	Insulation Paper	0.125mmx3T
6. Primary Terminal	Tin Plated Copper With Paper	1 Set
7. Primary Outer Wrap	Insulation Paper	0.25mmx1PC
8. Primary Outer Wrap	Mylar Tape	0.025mmx2T
9. Secondary Winding	Polyurethane Enameled Copper Wire	0.75 mm
10. Secondary Outer Wrap	Mylar Tape	0.025mmx2T



All information contained herein applies only to the above listed part number. Other versions of this part number with electrical or mechanical variations are available. Contact CUI Inc. for further assistance. 9615 SW Allen Blvd., Ste. 103, Beaverton OR 97005  
 800-275-4899 • 503-643-4899 • Fax: 503-643-6129 • www.cui.com

ITEM	SPEC	SAMPLE												
		1	2	3	4	5	6	7	8	9	10			
Primary Exciting Current Input 120VAC, 60Hz	100 mA max	34												
Primary Load Current Input 120VAC, 60Hz	240 mA max	191												
Secondary No Load DC Voltage	5 V ± 5%	5.37												
Secondary DC Voltage Load 1500mA	5V ± 5%	5.16												
Secondary Voltage Load mA	V ± %													
Secondary Voltage Load mA	V ± %													
Secondary Voltage Load mA	V ± %													
Ripple Voltage (PK-PK) Load 1500mA	50m V max	10												
Hi-Pot Test 2mA for 1Minute.	Pri. toSec	1.5 kvac	OK											
	Pri. to core	1.5 kvac	OK											
	Sec. to Core	1 kvac	OK											
Temperature Rise: 70° MAX Measured By Resistance Method (Primary Winding)														
Coil Form: SPLIT BOBBIN Core : EI- 57														
Testing Circuit:														
Output Plug Drawing: PLUG:5.5x2.1mm														
Output conductor length: 6 ft TYP. (AWG# 18SPT-1 )														
Input conductor length: 6 ft TYP. (AWG# 18SPT-2 3C )														
(V) Characteristic Curve														
(mA)														

SPEC NO: 035-0059

PART NO: DTR050150-P5



CUI INC

PAGE NO: 3 of 3

UNIT: mm

DATE: 06/22/00

All information contained herein applies only to the above listed part number. Other versions of this part number with electrical or mechanical variations are available. Contact CUI Inc. for further assistance. 9615 SW Allen Blvd., Ste. 103, Beaverton OR 97005  
800-275-4899 • 503-643-4899 • Fax: 503-643-6129 • [www.cui.com](http://www.cui.com)

