SMD ONE PORT 315.00 MHz SAW RESONATOR

ASR315E





> STANDARD SPECIFICATIONS:

CHARACTERISTICS			UNIT	MIN.	TYP.	MAX.	
Center Frequency Fo			MHz	314.925	315.000	315.075	
Tolerance from Fo			KHz		±75		
Insertion Loss			dB	-	1.4	2.0	
Quality Factor	Unloaded		-		10,750		
	50Ω loaded				1,600		
Temperature Stability	Turnover Temperature		°C	25.0		55	
	Turnover Frequency		KHz		Fo		
	Freq. Temp. Coefficient		ppm/°C2		0.03		
Frequency Aging			ppm/year		<±10		
DC Insulation Resistance			MΩ	1.0			
RF Equivalent RLC Model	Motional Resistance R ₁		Ω		17.5	26	
	Motional Inductance L₁		⊠H		95.0359		
	Motional Capacitance C ₁		fF		2.6889		
	Shunt Capacitance C ₀		pF	1.8	3.0	2.2	
Operating temp.		°C		-40°C to +85°C			
Storage temp.		°C		-45°C to +85°C			
Max. Rating	DC voltage	V	±30				
Soldering Temperature		°C	250				
RF Power Dissipation		dBm	0				

Data measured with: Source Impedance: Zs=50Ω, Load Impedance: ZL=50Ω, TA=25°C Electrostatic Sensitive Device. Handle with precaution.

-50

-10D

-150

> MARKING:


- 315.00 (315 Frequency in MHz) - AR ZYX (ZY: Date code Z for month

from A to L; Y for year, I.e. 4 for 2004


X: Traceability code)


PIN NO.	CONNECTIONS	
1	Input GND	
2	Input	
5	Output GND	
6	Output	
3,7	To be GNDed	
4,8	Case GND	

> OUTLINE DRAWING:



\triangleright	FREQU	JENCY	RESPO	NSE:





ATTENTION: Abracon Corporation's products are COTS - Commercial-Off-The-Shelf products; suitable for Commercial, Industrial and, where designated, Automotive Applications. Abracon's products are not specifically designed for Military, Aviation, Aerospace, Life-dependant Medical applications or any application requiring high reliability where component failure could result in loss of life and/or property. For applications requiring high reliability and/or presenting an extreme operating environment, written consent and authorization from Abracon Corporation is required. Please contact Abracon Corporation for more information.



