

**Ratings**

Voltage: 600 V  
 Temperature: -40~105 °C  
 Flammability: VW-1

**Conductor**

Conductor count: 1  
 Gauge: 20 AWG 0.52 mm<sup>2</sup>  
 Material: tinned copper strands  
 Strand size: Ø 0.16 mm x 26  
 Resistance at 20 °C: 36.7 Ω /km max


**Insulator**

Material: Polyphenylene Ether, Modified (mPPE)  
 Color: black  
 Diameter: Ø 1.5 ±0.10 mm  
 Nominal thickness: 0.26 mm  
 Resistance at 20 °C: 100 MΩ /km min

**Wire marking:** E339579 UL AWM STYLE 11028 20 AWG 105°C  
 600V VW-1 --- cUL AWM I A/B 105°C 600V FT1 TENSILITY

**Bend radius**

Minimum: 4 times diameter (6.0 mm)



Revision:	Date:	Description:	Prepared:	Notes:	<b>TENSILITY</b>
A	2/24/2021	Initial release	AG <small>Digitally signed by AG Date: 2021.02.24 12:34:37 -08'00'</small>		
			Verified:	Phthalate and halogen free	tel 1.541.323.3228 800 877.670.7118 fax 1.541.323.4202 web tensility.com
			AW <small>Digitally signed by AW Date: 2021.03.04 14:31:58 -08'00'</small>	Description:	Size: Part number:
			Dimensions are in millimeters.	Wire, hook-up, TS, 20 AWG, UL 11028, 600V, 105C, 1.5 mm, mPPE, black	A 30-01743
			Tolerances: X: ± 0.5 mm X.X: ± 0.3 mm X.XX: ± 0.05 mm		Scale: 20:1   Sheet 1 of 1

5

4

3

2

1