

MULTI-BEAM

TE Internal #: 3-6450170-8 Rectangular Power Connectors, Header, Receptacle, Board-to-Board, 42 Position, 2.54 mm [.1 in] Centerline, Printed Circuit Board, UL 94V-0

View on TE.com >

Connectors > Power Connectors > Rectangular Power > Rectangular Power Connectors



Rectangular Power Connector Type: Header Connector & Housing Type: Receptacle Connector System: Board-to-Board

Number of Positions: 42

Centerline (Pitch): 2.54 mm [.1 in]

Features



Product Type Features

Rectangular Power Connector Type	Header
Connector & Housing Type	Receptacle
Connector System	Board-to-Board
Sealable	No
Connector & Contact Terminates To	Printed Circuit Board
Configuration Features	
Number of Positions	42
PCB Mount Orientation	Right Angle
Number of Power Positions	2
Number of Signal Positions	40
Number of Rows	4
Electrical Characteristics	
Operating Voltage	60 VDC
Contact Features	

3-6450170-8

Rectangular Power Connectors, Header, Receptacle, Board-to-Board, 42 Position, 2.54 mm [.1 in] Centerline, Printed Circuit Board, UL 94V-0



Contact Mating Area Plating Material	Gold Flash over Palladium Nickel
Contact Underplating Material	Nickel
Contact Current Rating (Max)	42 A
Contact Retention Within Housing	Without
Contact Type	Receptacle
PCB Contact Termination Area Plating Material	Tin
Contact Mating Area Plating Material Thickness	.76 μm[30 μin]
Termination Features	
Termination Method to Printed Circuit Board	Through Hole - Solder
Mechanical Attachment	
Connector Mounting Type	Board Mount
Housing Features	
Centerline (Pitch)	2.54 mm[.1 in]
Housing Color	Black
Housing Material	High Temperature Thermoplastic
Dimensions	
Row-to-Row Spacing	2.54 mm[.1 in]

Usage Conditions

Operating Temperature Range	-20 – 105 °C[-4 – 221 °F]
Operation/Application	
Circuit Application	Power & Signal
Industry Standards	
UL Flammability Rating	UL 94V-0
Glow Wire Rating	High Temperature Part - Not Glow Wire
Packaging Features	
Packaging Method	Tray
Product Compliance For compliance documentation, visit the product page on TE.com>	
EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant

3-6450170-8

Rectangular Power Connectors, Header, Receptacle, Board-to-Board, 42 Position, 2.54 mm [.1 in] Centerline, Printed Circuit Board, UL 94V-0



China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JUNE 2023 (235) Does not contain REACH SVHC
Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.
Solder Process Capability	Wave solder capable to 265°C

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts



Customers Also Bought



Documents

Product Drawings MBXL R/A RCPT 1P+40S+1P

C For support call+1 800 522 6752

3-6450170-8

Rectangular Power Connectors, Header, Receptacle, Board-to-Board, 42 Position, 2.54 mm [.1 in] Centerline, Printed Circuit Board, UL 94V-0



English

CAD Files Customer View Model ENG_CVM_CVM_3-6450170-8_2.2d_dxf.zip English 3D PDF 3D Customer View Model ENG_CVM_CVM_3-6450170-8_2.3d_igs.zip English Customer View Model ENG_CVM_CVM_3-6450170-8_2.3d_stp.zip English

By downloading the CAD file I accept and agree to the Terms and Conditions of use.

Product Specifications Application Specification

English