BGA Heat Sink - High Performance maxiFLOW w/Thermal Tape





ATS Part#:

Description:

ATS-52375B-C1-R0

37.50 x 37.50 x 7.50 mm BGA Heat Sink - High Performance maxiFLOW w/Thermal Tape

Heat Sink Type:maxiFLOWHeat Sink Attachment:Thermal TapeEquivalent Part Number:ATS-52375B-C2-R0

*Image above is for illustration purpose only.

Features & Benefits

- maxiFLOW[™] design features a low profile, spread fin array that maximizes surface area for more effective convection (air) cooling
- Fabricated from extruded aluminum, which minimizes thermal resistance from the base to the fins, reduces weight and keeps costs low
- Higher performance helps ensure reliable product life at a lower cost than other extruded heat sinks

Thermal Performance

		@200 LFM 1.0 M/S	@300 LFM 1.5 M/S	@400 LFM 2.0 M/S	@500 LFM 2.5 M/S	@600 LFM 3.0 M/S	@700 LFM 3.5 M/S	@800 LFM 4.0 M/S
THERMAL RESISTANCE	Unducted Flow	4.9 °C/W	3.6 °C/W	3 °C/W	2.7 °C/W	2.5 °C/W	2.3 °C/W	2.1 °C/W
	Ducted Flow	3.3	N/A	N/A	N/A	N/A	N/A	N/A

Product Detail

Schematic Image	Dimension A	Dimension B	Dimension C	Dimension D	ТІМ	Finish
	37.50 mm	37.50 mm	7.50 mm	50.36 mm	T412	BLUE-ANODIZED
	 Dimension ATS-5237 (Saint-Gol Thermal p application ATS reser performan ATS certifier 	ves the right to upda	eight from the bottor act heat sink assemb e provided for referer ate or change its proo k assembly is RoHS	ly with an equivalen nce only. Actual perf ducts without notice -6 and REACH com	t thermal	interface material may vary by
*Image above is for illustration purpose only.						

For more information, to find a distributor or to place an order, please contact us at 781-769-2800 (North America), **sales@qats.com** or **www.qats.com**.

