



Main

Device Application	Heavy duty Universal mill switch Standard mill switch
Device short name	T
Series name	Severe duty

Complementary

[Ith] conventional free air thermal current	20 A
[Ui] rated insulation voltage	600 V
Base plate style	Style B
Body Material	Cast zinc
Contact code designation	P600 A600
Contacts material	Silver flashed copper
Contact operation	Snap action
Maximum displacement angle	90 °
Positive opening	Without
Stage of operation	Contact closed
Switch actuation	CW and CCW
Tilting angle	45 °
Torque Value	8 lbf.in (0.90 N.m)
Tripping angle	0 °

Environment

Ambient Air Temperature for Operation	-10...185 °F (-23...85 °C)
Electrical shock protection class	Class 0
IP Degree of Protection	IP65 IP66 IP67
NEMA Degree of Protection	NEMA 1/2/4/12/13
Product Certifications	CSA CE UL Listed
Protective treatment	Corrosion resistant gray paint
Shock resistance	30 gn
Standards	UL 508

Ordering and shipping details

Category	21497-9007 FT,T OILTIGHT AND FOUNDRY
Discount Schedule	DS1
GTIN	785901752110
Returnability	No
Country of origin	MX

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	3.50 in (8.89 cm)
Package 1 Width	6.40 in (16.256 cm)
Package 1 Length	2.90 in (7.366 cm)
Package 1 Weight	2.50 lb(US) (1.134 kg)

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACH Regulation	REACH Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile

Contractual warranty

Warranty	18 months
----------	-----------