

## Battery - STEP-BAT/LIPO/18.5DC/1.4AH - 2320364

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://download.phoenixcontact.com>)

Replacement battery module, lithium polymer, 18.5 V DC, 1.4 Ah.



### Key commercial data

Packing unit	1 pc
Weight per Piece (excluding packing)	280.0 GRM
Custom tariff number	85078000
Country of origin	China

### Technical data

#### Dimensions

Width	88 mm
Height	46 mm
Depth	51 mm

#### Ambient conditions

Degree of protection	IP20
Ambient temperature (operation)	0 °C ... 40 °C
Ambient temperature (storage/transport)	-20 °C ... 45 °C
Max. permissible relative humidity (operation)	≤ 95 % (25°C, non-condensing)

#### Input data

Nominal input voltage	18.5 V DC
-----------------------	-----------

#### Output data

Output current	6 A
Balancer circuit, internal	Yes
Protective circuit, internal	Yes

# Battery - STEP-BAT/LIPO/18.5DC/1.4AH - 2320364

## Technical data

### General

IQ technology	No
Net weight	0.22 kg
Memory medium	Lithium polymer, 1.4 Ah
Protection class	III

### Charging process

Charge current	400 mA
End-of-charge voltage	21 V DC

## Classifications

### eCl@ss

eCl@ss 4.0	27040603
eCl@ss 4.1	27040603
eCl@ss 5.0	27040603
eCl@ss 5.1	27040603
eCl@ss 6.0	27040603
eCl@ss 7.0	27040603
eCl@ss 8.0	27040603

### ETIM

ETIM 3.0	EC000382
ETIM 4.0	EC000382
ETIM 5.0	EC000357

### UNSPSC

UNSPSC 6.01	30211510
UNSPSC 7.0901	39121011
UNSPSC 11	39121011
UNSPSC 12.01	39121011
UNSPSC 13.2	39121011

## Approvals

### Approvals

---

### Approvals

IECEE CB Scheme / UL Recognized / cUL Recognized / cULus Recognized

# Battery - STEP-BAT/LIPO/18.5DC/1.4AH - 2320364

## Approvals

---

Ex Approvals

---

Approvals submitted

---

## Approval details

