



**Specification**



- Lever body  
Zinc die-cast
- Powder coated
  - Black, RAL 9005, textured finish ● **SW**
  - Orange, RAL 2004, textured finish ● **OS**
  - Red, RAL 3000, textured finish ● **RS**
  - Silver, RAL 9006, textured finish ● **SR**
- Chrome-plated finish ● **CR**
- Uncoated, tumbled finish ○ **RH**
- Threaded stud / retaining screw  
Stainless steel  
European Standard No. 1.4035 (AISI 303)
- RoHS compliant

**Information**

GN 300.1 adjustable levers have proven to be ideal wherever parts have to be clamped in a confined space or in a particular lever position. The insert is connected to the lever via serrations that can easily be disengaged.

Pulling the lever upwards disengages the serrations, allowing it to be swiveled to the ideal clamping position. When releasing the lever, the serrations automatically re-engage.

see also...

- *Adjustable Levers GN 300 (with Steel Threaded Stud)*
- *Adjustable Levers GN 300.5 (Stainless Steel, Matte Shot-Blasted Finish)*
- *Adjustable Levers GN 303.1 (with Push Button)*

**On request**

- Black, RAL 9011, silk shiny finish ● **SZ**
- Special colors, stud lengths, and threads

How to order (Inch)	1 <b>Lever length l<sub>1</sub></b>
<span style="color: red;">1</span> <span style="color: red;">2</span> <span style="color: red;">3</span> <span style="color: red;">4</span>	2 <b>Thread d<sub>1</sub></b>
<b>GN 300.1-92-1/2X13-40-SW</b>	3 <b>Thread length l<sub>2</sub></b>
	4 <b>Color (Finish)</b>

How to order (Metric)	1 <b>Lever length l<sub>1</sub></b>
<span style="color: red;">1</span> <span style="color: red;">2</span> <span style="color: red;">3</span> <span style="color: red;">4</span>	2 <b>Thread d<sub>1</sub></b>
<b>GN 300.1-63-M8-32-RS</b>	3 <b>Thread length l<sub>2</sub></b>
	4 <b>Color (Finish)</b>

**Inch table**

Dimensions in: inches - millimeters

<sup>1</sup> l <sub>1</sub>	<sup>2</sup> d <sub>1</sub> Thread	<sup>3</sup> l <sub>2</sub>									d <sub>3</sub>	d <sub>4</sub>	h <sub>1</sub>	h <sub>2</sub>	h <sub>3</sub>	h <sub>4</sub> Stroke
1.18 30	10 x 32	.47 12	.63 16	.79 20	-	-	-	-	-	-	.39 10	.51 13	.96 24.5	.16 4	1.22 31	.14 3.5
1.18 30	10 x 24	.47 12	.63 16	.79 20	.98 25	1.26 32	-	-	-	-	.39 10	.51 13	.96 24.5	.16 4	1.22 31	.14 3.5
1.18 30	1/4 x 20	.47 12	.63 16	.79 20	.98 25	1.26 32	1.57 40	1.77 45	-	-	.39 10	.51 13	.96 24.5	.16 4	1.22 31	.14 3.5
1.77 45	10 x 32	.47 12	.63 16	.79 20	.98 25	1.26 32	-	-	-	-	.39 10	.51 13	.96 24.5	.16 4	1.34 34	.14 3.5
1.77 45	10 x 24	.63 16	-	-	-	-	-	-	-	-	.39 10	.51 13	.96 24.5	.16 4	1.34 34	.14 3.5
1.77 45	1/4 x 20	.47 12	.63 16	.79 20	.98 25	1.26 32	1.57 40	1.77 45	-	-	.39 10	.51 13	.96 24.5	.16 4	1.34 34	.14 3.5
2.48 63	5/16 x 18	.63 16	.79 20	.98 25	1.26 32	1.57 40	1.77 45	1.97 50	2.48 63	-	.53 13.5	.69 17.5	1.22 31	.26 6.5	1.77 45	.16 4
2.48 63	3/8 x 16	.79 20	.98 25	1.26 32	1.57 40	-	-	-	-	-	.53 13.5	.69 17.5	1.22 31	.26 6.5	1.77 45	.16 4
3.07 78	3/8 x 16	.79 20	.98 25	1.26 32	1.57 40	1.77 45	1.97 50	2.48 63	-	-	.63 16	.83 21	1.42 36	.31 8	2.13 54	.16 4
3.07 78	1/2 x 13	.79 20	.98 25	1.26 32	1.57 40	1.97 50	-	-	-	-	.63 16	.83 21	1.42 36	.31 8	2.13 54	.16 4
3.62 92	1/2 x 13	.98 25	1.26 32	1.57 40	1.77 45	1.97 50	2.48 63	-	-	-	.75 19	.94 24	1.69 43	.43 11	2.52 64	.16 4

**Metric table**

Dimensions in: millimeters - inches

<sup>1</sup> l <sub>1</sub>	<sup>2</sup> d <sub>1</sub> Thread	<sup>3</sup> l <sub>2</sub>									d <sub>3</sub>	d <sub>4</sub>	h <sub>1</sub>	h <sub>2</sub>	h <sub>3</sub>	h <sub>4</sub> Stroke
30 1.18	M 3	-	-	6 .24	8 .31	10 .39	12 .47	16 .63	-	-	10 .39	13 .51	24.5 .96	4 .16	31 1.22	3.5 .14
30 1.18	M 4	-	-	12 .47	16 .63	20 .79	25 .98	32 1.26	-	-	10 .39	13 .51	24.5 .96	4 .16	31 1.22	3.5 .14
30 1.18	M 5	M 6	-	12 .47	16 .63	20 .79	25 .98	32 1.26	40 1.57	50 1.97	10 .39	13 .51	24.5 .96	4 .16	31 1.22	3.5 .14
45 1.77	M 4	-	-	12 .47	16 .63	20 .79	25 .98	32 1.26	-	-	10 .39	13 .51	24.5 .96	4 .16	34 1.34	3.5 .14
45 1.77	M 5	M 6	-	12 .47	16 .63	20 .79	25 .98	32 1.26	40 1.57	50 1.97	10 .39	13 .51	24.5 .96	4 .16	34 1.34	3.5 .14
63 2.48	M 6	M 8	-	16 .63	20 .79	25 .98	32 1.26	40 1.57	50 1.97	63 2.48	13.5 .53	17.5 .69	31 1.22	6.5 .26	45 1.77	4 .16
78 3.07	M 8	M 10	M 12	20 .79	25 .98	32 1.26	40 1.57	50 1.97	63 2.48	80 3.15	16 .63	21 .83	36 1.42	8 .31	54 2.13	4 .16
92 3.62	M 10	M 12	-	20 .79	25 .98	32 1.26	40 1.57	50 1.97	63 2.48	80 3.15	19 .75	24 .94	43 1.69	11 .43	64 2.52	4 .16
108 4.25	M 12	M 16	-	32 1.26	40 1.57	50 1.97	63 2.48	80 3.15	-	-	23 .91	30 1.18	50.5 1.99	12 .47	75 2.95	5 .20

1.1  
1.2  
1.3  
1.4  
2.1  
2.2  
2.3  
2.4

