

4

3

2

1

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

20

© COPYRIGHT 20

BY TE CONNECTIVITY

ALL RIGHTS RESERVED.

REVISIONS

変更

P	LTR	DESCRIPTION	DATE	DWN	APVD
	C	REVISED	28APR2014	T.S	N.Y

0.7  
0.33

1.3  
1.08 REF

2.3  
1.67 REF

-2:本図  
-2:AS SHOWN

AA - AA  
SCALE 20:1

AB - AB  
SCALE 20:1

1.8  
0.8  
5.9  
AA  
AB  
AB  
AA

1 材料:黄銅

2 仕上げ:全面ニッケル下地めっき  
接触部及び圧着部に0.2μm以上の金めっき

3 AWG#26, AWG#28対応

対応電線: UL1571 AWG#26	対応電線: UL1571 AWG#28
素線数/素線径: 7/0.16mm <sup>2</sup>	素線数/素線径: 7/0.127mm <sup>2</sup>
絶縁被覆径: $\phi$ 0.94- $\phi$ 1.20	絶縁被覆径: $\phi$ 0.84- $\phi$ 0.92

1 MATERIAL: BRASS

2 FINISH: Ni UNDER PLATING ALL SURFACE  
CONTACT AND CRIMP AREA: Au PLATING 0.2μm MIN.

3 WIRE SIZE AWG#26, AWG#28

APPLICABLE WIRES: UL1571 AWG#26	APPLICABLE WIRES: UL1571 AWG#28
NUMBER OF CONDUCTORS/ DIAMETER OF A CONDUCTOR: 7/0.16mm <sup>2</sup>	NUMBER OF CONDUCTORS/ DIAMETER OF A CONDUCTOR: 7/0.127mm <sup>2</sup>
INSULATION DIAMETER: $\phi$ 0.94- $\phi$ 1.20	INSULATION DIAMETER: $\phi$ 0.84- $\phi$ 0.92

THIS DRAWING IS A CONTROLLED DOCUMENT.

DWN 18MAY2010

H. URUSHIBATA

CHK 18MAY2010

N. YAMASAKI

APVD 18MAY2010

T. MASUDA

PRODUCT SPEC

108-78658

APPLICATION SPEC

114-5446

WEIGHT -

WIRE RANGE  
抱合電線断面積

3

INSULATION DIA  
被覆外径

4

TE Connectivity

NAME

名称  
POST CONTACT  
1.5VP REMODEL

SIZE

CAGE CODE

DRAWING NO  
番号

RESTRICTED TO

A3

-

C-2069391

-

DIMENSIONS:  
単位: 概  
mm

TOLERANCES UNLESS  
OTHERWISE SPECIFIED:

一般公差 ±0.2  
0 PLC ±  
1 PLC ±0.5  
2 PLC ±0.13  
3 PLC ±0.013  
4 PLC ±0.000J  
ANGLES ±1

MATERIAL  
材料

1

FINISH  
仕上

2

1470-19 (3/13)