

October 2009

FJAF4210 PNP Epitaxial Silicon Transistor

Features

- · Audio Power Amplifier
- High Current Capability: I_C= -10A
- · High Power Dissipation
- Wide S.O.A
- Complement to FJAF4310



Absolute Maximum Ratings* $T_A=25$ °C unless otherwise noted

Symbol	Parameter	Value	Units
V _{CBO}	Collector-Base Voltage	-200	V
V _{CEO}	Collector-Emitter Voltage	-140	V
V _{EBO}	Emitter-Base Voltage	-6	V
I _C	Collector Current (DC)	-10	Α
I _B	Base Current (DC)	-1.5	Α
P _C	Collector Dissipation (T _C =25°C)	80	W
$R_{ heta JC}$	Junction to Case	1.33	°C/W
T _J	Junction Temperature	150	°C
T _{STG}	Storage Temperature	- 55 ~ 150	°C

Electrical Characteristics $T_A=25$ °C unless otherwise noted

Symbol	Parameter	Test Condition	Min.	Тур.	Max.	Units
BV _{CBO}	Collector-Base Breakdown Voltage	I_C =-5mA, I_E =0	-200			V
BV _{CEO}	Collector-Emitter Breakdown Voltage	I_C =-50mA, R_{BE} = ∞	-140			V
BV _{EBO}	Emitter-Base Breakdown Voltage	I_E =-5mA, I_C =0	-6			V
I _{CBO}	Collector Cut-off Current	V _{CB} =-200V, I _E =0			-10	μΑ
I _{EBO}	Emitter Cut-off Current	V_{EB} =-6V, I_{C} =0			-10	μΑ
h _{FE}	* DC Current Gain	V_{CE} =-4V, I_{C} =-3A	50		180	
V _{CE} (sat)	Collector-Emitter Saturation Voltage	I _C =-5A, I _B =-0.5A			-0.5	V
C _{ob}	Output Capacitance	V _{CB} =-10V, f=1MHz		400		pF
f _T	Current Gain Bandwidth Product	V_{CE} =-5V, I_{C} =-1A		30		MHz

^{*} Pulse Test : PW=20µs

h_{FE} Classification

Classification	R	0	Y	
h _{FE}	50 ~ 100	70 ~ 140	90 ~ 180	

Typical Perpormance Characteristics




Figure 1. Static Characterstic




Figure 3. V_{CE}(sat) vs. I_B Characteristics




Figure 5. Base-Emitter On Voltage




Figure 2. DC current Gain




Figure 4. Collector-Emitter Saturation Voltage




Figure 6. Forward Bias Safe Operating Area

Typical Perpormance Characteristics

(Continued)





Figure 7. Power Derating

Physical Dimension

TO-3PF



Dimensions in Millimeters





TRADEMARKS

The following includes registered and unregistered trademarks and service marks, owned by Fairchild Semiconductor and/or its global subsidiaries, and is not intended to be an exhaustive list of all such trademarks.

AccuPower™ **FPS™** F-PFS™ Auto-SPM™ Build it Now™ FRFET®

Global Power ResourceSM CorePLUS™

CorePOWER™ Green FPS™

CROSSVOLT™ Green FPS™ e-Series™ CTL™ $Gmax^{TM}$

Current Transfer Logic™ EcoSPARK® $\mathsf{GTO}^{\mathsf{TM}}$ IntelliMAX™ EfficentMax™ ISOPLANAR™ EZSWITCH™* MegaBuck™

 $\mathsf{MICROCOUPLER}^{\scriptscriptstyle\mathsf{TM}}$ MicroFET™ MicroPak™ $Miller Drive^{TM}$ Fairchild® MotionMax™ Fairchild Semiconductor® Motion-SPM™ FACT Quiet Series™ FACT₋ OPTOLOGIC® OPTOPLANAR®

FAST® FastvCore™ FETBench™ PDP SPM™ FlashWriter®*

PowerTrench® PowerXS™ Programmable Active Droop™ QFĔT⁰

QS™ Quiet Series™ RapidConfigure™

Saving our world, 1mW/W/kW at a time™

SmartMax™ SMART START™ SPM® STEALTH™

SuperFET™ SuperSOT™-3 SuperSOT™-6 SuperSOT™-8 SupreMOS™ SyncFET™

Sync-Lock™
SYSTEM® GENERAL

The Power Franchise®

puwer TinyBoost™ TinyBuck™ TinyCalc™ TinyLogic[®] TINYOPTO™ TinyPower™ TinyPWM™ TinyWire™ TriFault Detect™ TRUECURRENT™* μSerDes™

LIHC Ultra FRFET™ UniFFT™ VCX™ VisualMax™ XSTM

Power-SPM™

DISCLAIMER

FAIRCHILD SEMICONDUCTOR RESERVES THE RIGHT TO MAKE CHANGES WITHOUT FURTHER NOTICE TO ANY PRODUCTS HEREIN TO IMPROVE RELIABILITY, FUNCTION, OR DESIGN. FAIRCHILD DOES NOT ASSUME ANY LIABILITY ARISING OUT OF THE APPLICATION OR USE OF ANY PRODUCT OR CIRCUIT DESCRIBED HEREIN; NEITHER DOES IT CONVEY ANY LICENSE UNDER ITS PATENT RIGHTS, NOR THE RIGHTS OF OTHERS. THESE SPECIFICATIONS DO NOT EXPAND THE TERMS OF FAIRCHILD'S WORLDWIDE TERMS AND CONDITIONS, SPECIFICALLY THE WARRANTY THEREIN, WHICH COVERS THESE PRODUCTS.

LIFE SUPPORT POLICY

FAIRCHILD'S PRODUCTS ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT THE EXPRESS WRITTEN APPROVAL OF FAIRCHILD SEMICONDUCTOR CORPORATION.

- 1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body or (b) support or sustain life, and (c) whose failure to perform when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in a significant injury of the user.
- 2. A critical component in any component of a life support, device, or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

ANTI-COUNTERFEITING POLICY

Fairchild Semiconductor Corporation's Anti-Counterfeiting Policy. Fairchild's Anti-Counterfeiting Policy is also stated on our external website, www.fairchildsemi.com, under Sales Support.

Counterfeiting of semiconductor parts is a growing problem in the industry. All manufacturers of semiconductor products are experiencing counterfeiting of their parts. Customers who inadvertently purchase counterfeit parts experience many problems such as loss of brand reputation, substandard performance, failed applications, and increased cost of production and manufacturing delays. Fairchild is taking strong measures to protect ourselves and our customers from the proliferation of counterfeit parts. Fairchild strongly encourages customers to purchase Fairchild parts either directly from Fairchild or from Authorized Fairchild Distributors who are listed by country on our web page cited above. Products customers buy either from Fairchild directly or from Authorized Fairchild Distributors are genuine parts, have full traceability, meet Fairchild's quality standards for handling and storage and provide access to Fairchild's full range of up-to-date technical and product information. Fairchild and our Authorized Distributors will stand behind all warranties and will appropriately address any warranty issues that may arise. Fairchild will not provide any warranty coverage or other assistance for parts bought from Unauthorized Sources. Fairchild is committed to combat this global problem and encourage our customers to do their part in stopping this practice by buying direct or from authorized distributors.

PRODUCT STATUS DEFINITIONS

Definition of Terms

Definition of Terms				
Datasheet Identification	Product Status	Definition		
Advance Information	Formative / In Design	Datasheet contains the design specifications for product development. Specifications may change in any manner without notice.		
Preliminary	First Production	Datasheet contains preliminary data; supplementary data will be published at a later date. Fairchild Semiconductor reserves the right to make changes at any time without notice to improve design.		
No Identification Needed	Full Production	Datasheet contains final specifications. Fairchild Semiconductor reserves the right to make changes at any time without notice to improve the design.		
Obsolete	Not In Production	Datasheet contains specifications on a product that is discontinued by Fairchild Semiconductor. The datasheet is for reference information only.		

Rev. I41

^{*} Trademarks of System General Corporation, used under license by Fairchild Semiconductor.