




- NOTES:
1. MATERIAL: GLASS-FILLED POLYESTER UL RATED 94V-0  
COLOR: BLACK
  2. PART TO BE USED WITH CRIMP TERMINAL  
PART NUMBER 50394-8\*\*\* AND 87396-\*\*\*\*
  3. APPLICABLE WIRE RANGE:  
FOR 50394 SERIES, AWG #24 - #30,  
FOR 87396 SERIES, AWG #22 - #28.
  4. WIRE INSULATION RANGE: DIAMETER 1.40MM MAXIMUM.
  5. 30 CKT SHOWN FOR ILLUSTRATION ONLY.



FUNCTIONAL SYMBOLS	THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX ELECTRONIC TECHNOLOGIES, LLC AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION		CURRENT REV DESC: RE-MASTERED IN NX/ECTR		<b>molex</b>		
	0	mm					
	0	GENERAL TOLERANCES (UNLESS SPECIFIED)		EC NO: 672815		2021/04/27	
	0	ANGULAR TOL ± 3.0°		DRWN: ABABUPS		2021/08/06	
DIVISIONAL SYMBOLS	4 PLACES	±	CHK'D: MRAMAKRISHNA		2021/08/06		PRODUCT CUSTOMER DRAWING
	3 PLACES	±	APPR: MRAMAKRISHNA		2021/08/06		
	2 PLACES	±	INITIAL REVISION:		DOCUMENT NUMBER		DOC TYPE
	1 PLACE	±	DRWN: SKTOH		1993/10/26		DOC PART
0 PLACES	±	APPR: LBLEE		2014/07/22		REVISION	
DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		THIRD ANGLE PROJECTION		DRAWING	SERIES	MATERIAL NUMBER	CUSTOMER
				B-SIZE	51110	SEE TABLE	GENERAL MARKET
							SHEET NUMBER
							1 OF 2

WITHOUT CENTER POLARIZATION KEY & SIDE LATCHES

PART NUMBER	CKT SIZE	DIM X	DIM Y
51110-0450	4	2.00	4.20
51110-0650	6	4.00	6.20
51110-0850	8	6.00	8.20
51110-1050	10	8.00	10.20
51110-1250	12	10.00	12.20
51110-1450	14	12.00	14.20
51110-1650	16	14.00	16.20
51110-1850	18	16.00	18.20
51110-2050	20	18.00	20.20
51110-2250	22	20.00	22.20
51110-2450	24	22.00	24.20
51110-2650	26	24.00	26.20
51110-2850	28	26.00	28.20
51110-3050	30	28.00	30.20
51110-3250	32	30.00	32.20
51110-3450	34	32.00	34.20

WITH CENTER POLARIZATION KEY & SIDE LATCHES

PART NUMBER	CKT SIZE	DIM X	DIM Y	DIM Z
51110-1451	14	12.00	14.20	8.00
51110-1651	16	14.00	16.20	10.00
51110-1851	18	16.00	18.20	12.00
51110-2051	20	18.00	20.20	14.00
51110-2251	22	20.00	22.20	16.00
51110-2451	24	22.00	24.20	18.00
51110-2651	26	24.00	26.20	20.00
51110-2851	28	26.00	28.20	22.00
51110-3051	30	28.00	30.20	24.00
51110-3251	32	30.00	32.20	26.00
51110-3451	34	32.00	34.20	28.00

WITH CENTER POLARIZATION KEY

PART NUMBER	CKT SIZE	DIM X	DIM Y
51110-0452	4	2.00	4.20
51110-0652	6	4.00	6.20
51110-0851	8	6.00	8.20
51110-1051	10	8.00	10.20
51110-1251	12	10.00	12.20
51110-1452	14	12.00	14.20
51110-1652	16	14.00	16.20
51110-1852	18	16.00	18.20
51110-2052	20	18.00	20.20
51110-2252	22	20.00	22.20

PART NUMBER LEGEND:

51110 - \*\* 5 \*

CIRCUIT SIZE

0 - WITHOUT CENTER POLARIZATION KEY AND SIDE LATCH.

1 - WITH CENTER POLARIZATION KEY AND SIDE LATCH.  
(14 TO 34 CIRCUITS ONLY)  
WITH CENTER POLARIZATION KEY ONLY.  
(8 TO 12 CIRCUITS ONLY)

2 - WITH CENTER POLARIZATION KEY ONLY.  
(4 TO 6 CIRCUITS AND 14 TO 22 CIRCUITS ONLY)

FUNCTIONAL SYMBOLS	THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX ELECTRONIC TECHNOLOGIES, LLC AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION		CURRENT REV DESC: RE-MASTERED IN NX/ECTR		<b>molex</b>		
	DIMENSION UNITS	SCALE					
$\nabla/A = 0$	mm	NTS	GENERAL TOLERANCES (UNLESS SPECIFIED)		2MM GRID, WIRE TO BOARD CONNECTOR, CRIMP RECEPT. HOUSING		
$\nabla/E = 0$	ANGULAR TOL $\pm 3.0^\circ$						
$\nabla/P = 0$	4 PLACES $\pm$						
DIVISIONAL SYMBOLS	3 PLACES $\pm$		EC NO: 672815		2021/04/27		
	2 PLACES $\pm 0.2$		DRWN: ABABUPS		2021/08/06		
	1 PLACE $\pm$		CHK'D: MRAMAKRISHNA		2021/08/06		
	0 PLACES $\pm$		APPR: MRAMAKRISHNA		2021/08/06		
DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		THIRD ANGLE PROJECTION		DRAWING		SERIES	
				A3-SIZE		51110	
				MATERIAL NUMBER		CUSTOMER	
				SEE TABLE		GENERAL MARKET	
				DOCUMENT NUMBER		DOC TYPE   DOC PART   REVISION	
				SD-51110-XX5X		PSD   001   B10	
				INITIAL REVISION:		SHEET NUMBER	
				DRWN: SKTOH		2 OF 2	
				APPR: LBLEE			