

**PROPRIETARY INFORMATION:**  
 PROPRIETARY OF GLOBTEK, INC. ANY REPRODUCTION, DISCLOSURE OR USE OF THIS DRAWING, IN WHOLE OR IN PART, IS HEREBY PROHIBITED EXCEPT AS SPECIFIED IN WRITING BY GLOBTEK, INC.

REVISION			
REV	DESCRIPTION	DATE	APPROVED
A	INITIAL RELEASE, RFS. 25489, SO	04/21/14	HM
B	CLARIFY VIEW 'A' POLARITY RECEPTACLE 'LINE' AND 'NEUTRAL', RFS.27322	04/25/19	HM



'A'



'B'



**GENERAL SPECIFICATIONS:**

RATING: 10A / 250V AC  
 CABLE TYPE / SIZE: SVT, # 18 AWG, 3 CONDUCTOR  
 SHIELDED/ EUROPEAN COLOR CODED CONDUCTORS  
 TEMPERATURE RATING: 75° C MINIMUM  
 CONDUCTOR COLORS: BLUE / BROWN / GREEN-YELLOW  
 CABLE JACKET COLOR: BLACK  
 OVERALL LENGTH: 1830 ± 25 mm  
 CABLE OUTER DIAMETER: 6.3 ± 0.1 mm  
 END 'A' PLUG: IEC-320 / C13  
 END 'B' : SEE TERMINATION TABLE  
 APPROVALS PLUG: UL, CSA or cUL  
 APPROVALS CABLE: UL, CSA or cUL



**PACKING:**

BULK PACKED, BUNDLES OF 25.  
 MAXIMUM SHIPPING CARTON WEIGHT IS 30 KG.

**CONDUCTOR TERMINATION TABLE:**

Wire	Color	ROJ ± 5 mm	RIJ ± 0.5 mm	Termination
Neutral	Bue	51	16	Stripped
Line	Brown	51	16	Stripped
Ground	Green-Yellow	51	16	Stripped

**NOTES:**

1. CORD AND PLUG MUST BE MARKED WITH APPROVAL SYMBOLS AND/ OR FILE NUMBERS.
2. SHIELD IS CONNECTED TO GROUND PIN ON IEC 320/C13.



**RELEASED**  
 By N.Frost at 3:33 pm, Apr 25, 2019

DASH NO.	PART NO	REV.	DESCRIPTION	NOTES
<b>TABULATION BLOCK</b>				
		<b>TOLERANCES:</b> DECIMALS ANGULAR .xx +/- 0.1 +/- 1° .xxx +/- .005		<b>GlobTek, Inc.</b> www.globtek.com 186 Veterans Dr. Northvale, NJ 07647 Tel. 201-784-1000 Fax 201.784.0111
		MILLIMETERS ANGULAR .xx +/- 0.3 +/- 1° .xxx +/- .013		
INIT.BY: SO	DATE: 04/21/14	DWG TITLE: NON-DETACHABLE CORDSET		
DRAWN: NF	DATE: 04/21/14	FSCN No.: G, CC	SIZE: A	REV. B
APRVD: HM	DATE: 04/21/14	SCALE: NONE	PART NO: 7011876F000-CEE(R)	SHEET 1/1

Foot Note:  
 Globtek Inc. will not be liable for the safety and performance of these power product if unauthorized access and repair occurs. End user should consult the applicable UL, CSA or EN Standards for proper installation instruction.

Limitation of Use:  
 Globtek product are not authorized for use as mission critical components in life support, hazardous environment, nuclear or aircraft applications without prior written approval from the CEO of Globtek Inc.

Contents of this document are subject to change without prior notice