




Units: mm



Electrical test:

1. 100% short, open, miswire test
2. Conduct resistance: 5 Ohm(max)
3. Insulation resistance: 10Mohm(min)
4. dielectric test: DC 300V



⑧	TIE	2	BLACK L=80mm
⑦	PE BAG	1/10	CLEAR SIZE: 280*330*0.05mm PRINT BLACK"MADE IN CHINA"+"10PCS"
⑥	PE BAG	1	CLEAR SIZE: 130*230*0.05mm PRINT BLACK"MADE IN CHINA"+"1PC"
⑤	S/R	3.0g	BLACK PVC 40P (Mould NO.:SR-048)
④	IN JACKET	1.6g	CLEAR LD-PE (Mould NO.:NM-006)
	OUT JACKET	6.6g	PVC-40P RED(RD-35),(Mould NO.WM-009)
③	IN JACKET	1.6g	CLEAR LD-PE (Mould NO.:NM-006)
	OUT JACKET	6.6g	PVC-40P WHITE(W-100)(Mould NO.WM-009)
②	CABLE	1	NOUL 28#(10/0.10+28/0.10)*2F JACKET BLACK OD2.8*5.6mm
①	CONN	4	RCA PLUG MALE 梅花型 TYPE NI-PLATED INSULATOR COLOR:BROWN
NO.	NAME	QTY	SPECIFICATION

CnC Tech, LLC

Industrial Cable and Connector Technology

DRAWN BY	LICHENG	DRAWING NO.	VG/LJ0-094-082-C
CHECKED BY		CUSTOMER	CnC
APPROVAL BY		ITEM NO.	770-20011-00200
DECIDE BY		DATE	2012-12-28
VERSIONS/EDITEON	A/0	PROJECTION	

NOTE:
1.小PE袋大PE袋对应料号,包装袋数量及时间印刷样式:
CnC Tech, LLC
Industrial Cable and Connector Technology
770-20011-00200
10 PCS
ROHS 529
印家A/0料号
印刷件数量
表示529099年(依每个产品生产周期)

2.外箱两个侧袋ITEM NO后面各贴一个35*22mm ROHS标签。