

Aug. 1.2023 Copyright 2023 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
 In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.

APPLICABLE STANDARD			
RATING	OPERATING TEMPERATURE RANGE	-25 °C TO 60 °C	STORAGE TEMPERATURE RANGE -25 °C TO 60 °C
	VOLTAGE		CURRENT
SPECIFICATIONS			
ITEM	TEST METHOD	REQUIREMENTS	QT AT
CONSTRUCTION			
GENERAL EXAMINATION	VISUALLY AND BY MEASURING INSTRUMENT.	ACCORDING TO DRAWING.	X X
MARKING	CONFIRMED VISUALLY.		X X
COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED DATE
2	DIS-E-00002227	TS. ITO	TU. TANIGUCHI 20190418
REMARK		APPROVED	HO. MIWA 20050105
PACKING MATERIAL IS NOT INCLUDED.		CHECKED	TH. KAMEYA 20050105
Unless otherwise specified, refer to JIS C 5402.		DESIGNED	SS. SATOH 20050105
		DRAWN	SS. SATOH 20050105
Note QT:Qualification Test AT:Assurance Test X:Applicable Test		DRAWING NO.	ELC4-121484-01
HRS	SPECIFICATION SHEET	PART NO.	TM21P-88P (**)
	HIROSE ELECTRIC CO., LTD.	CODE NO.	1/1