

## Han® S 200 FC CRT 50 mm<sup>2</sup> w. rubb. sleeve



Image is for illustration purposes only. Please refer to product description.

Part number	09 93 000 6264
Specification	Han® S 200 FC CRT 50 mm <sup>2</sup> w. rubb. sleeve
HARTING eCatalogue	<a href="https://b2b.harting.com/09930006264">https://b2b.harting.com/09930006264</a>

### Version

Manufacturing process	Turned contacts
-----------------------	-----------------

### Technical characteristics

Conductor cross-section	50 mm <sup>2</sup>
Conductor cross-section	AWG 1/0
Operating current	≤200 A
Contact resistance	≤0.3 mΩ
Stripping length	22 mm

### Material properties

Material (contacts)	Copper alloy
Surface (contacts)	Silver plated
Material (accessories)	Thermoplastic polyurethane (TPU)
RoHS	compliant
ELV status	compliant
China RoHS	e
REACH Annex XVII substances	Not contained
REACH ANNEX XIV substances	Not contained
REACH SVHC substances	Not contained
California Proposition 65 substances	Not contained



**Pushing Performance**  
Since 1945

## Specifications and approvals

Specifications	IEC 60664-1
	IEC 61984

## Commercial data

Packaging size	1
Net weight	47.2 g
Country of origin	China
European customs tariff number	85366990
GTIN	5713140188808
eCl@ss	27440204 Contact for industrial connectors